Client-Side Counter-Sycophancy Firewalls: Envelope Judge Recalibration and Prosody-Gated Dissent Preservation in Multi-Turn Personal AI

Dima Baker
Collective Intelligence Network

November 2026

Abstract

Preference-based post-training (RLHF and DPO) systematically amplifies language model sycophancy, teaching assistants to affirm a user's stated premise even when it is factually incorrect. While single-turn benchmarks (SycophancyEval, SYCON-Bench) document baseline flip rates near $\rho_0 = 58.1\%$ under user challenge, multi-turn dialogues introduce compounding conversational and prosodic/rhetorical insistence ($\tilde{a}_t$) that erodes static system-prompt guardrails. Conversely, naively penalizing the counterfactual log-likelihood gap $|\log \pi(y \mid x_t, \theta_u) - \log \pi(y \mid x_t, \neg\theta_u)|$ favors stance-neutral hedging even when the user's premise is true, inducing severe *false contrarianism*. We present an architectural synthesis and conditional candidate-score analysis of **CSF-Prosody**, a client-side counter-sycophancy firewall adapting post-training Envelope Judge Recalibration to inference-time reranking. By gating the counterfactual stance penalty with both a lower-envelope factual verification margin and observed prosodic/rhetorical pressure $\tilde{a}_{\text{obs},t}$ using observable candidate scores, CSF-Prosody suppresses sycophantic flips without contradicting true premises. Across 21,600 simulated dialogues spanning six architectures and horizons $T \in \{5, 10, 20, 40\}$ under calm-but-wrong, stressed-but-right, and verifier-misconception confounds, CSF-Prosody reduces $T = 20$ sycophantic flips from 80.00% ([76.61, 83.01], unfiltered RLHF), 69.17% ([65.36, 72.73], prompt guard), and 10.17% ([8.00, 12.84], verifier-only) to 1.50% ([0.79, 2.83]), while cutting true-premise false contrarianism from 76.67% ([71.56, 81.10], unconditional stance penalty) and 38.67% ([33.33, 44.29], prosody-only) to 7.00% ([4.62, 10.46]).

1 Introduction

As conversational AI assistants become the primary analytical interface for personal financial, medical, and civic decision-making, human epistemic autonomy faces a well-documented structural hazard: *sycophantic belief reinforcement*. Foundational work in psychology and human–computer interaction—including Self-Determination Theory [5, 21], Cognitive Load Theory [25], and large-scale empirical crawls of manipulative web "dark patterns" [10, 14]—established that human judgment is highly sensitive to environmental framing and social validation. Whereas commercial web interfaces manipulate choices externally through asymmetric click friction [14], personal language model assistants exert influence internally through conversational agreement bias.

1.1 Empirical and theoretical foundations of RLHF sycophancy

In foundational evaluations across five frontier model families (**SycophancyEval**), Sharma et al. [23] demonstrated that RLHF-trained assistants consistently tailor their explanations to match a

user's stated opinion and abandon correct factual answers when challenged with "Are you sure?" ($\rho_0 \approx 58.1\%$ single-shot flip rate on contested queries). While Wei et al. [26] showed that simple synthetic fine-tuning data can partially reduce single-turn opinion agreement on fixed templates, subsequent 2025–2026 theoretical and empirical studies proved that sycophancy is an emergent structural byproduct of preference optimization itself [9, 15, 19].

Specifically, Shapira et al. [22] proved mathematically that when a language model policy is optimized via KL-regularized reinforcement learning against a Bradley-Terry reward model learned from human preference comparisons, small annotator biases toward agreeable responses are exponentially amplified as the inverse temperature $1/\beta$ increases. This theoretical mechanism explains high-profile production incidents, such as OpenAI's 2025 post-mortem on extreme sycophantic validation in deployed chat models [16], as well as controlled economic and behavioral experiments conducted in 2026:

- **Degradation of incentivized human decisions:** Conlon and Schwardmann [3] show in incentivized decision experiments that sycophantic AI feedback significantly reduces human decision accuracy while inflating subjective confidence in erroneous choices.
- **Erosion of prosociality and critical independence:** Cheng et al. [2] demonstrate that interacting with sycophantic models reduces users' prosocial repair intentions and fosters psychological dependence on the assistant.
- **Diminished critical verification under cognitive load:** Complementary studies link uncritical reliance on agreeable AI outputs to reduced self-reported critical thinking [13], verification collapse under time constraints [27], "confidence without competence" [6], and the widening *Cognitive Divergence* between expanding model context windows and fixed human attention [7]. (While Kosmyna et al. [12] also reported EEG "cognitive debt" during LLM essay writing, Stanković et al. [24] provide an essential methodological critique noting small sample sizes and task confounds, whereas structured mastery tutoring significantly improves learning [11, 17] compared to unguarded answer access [1, 20].)

1.2 Why static prompt guards and naive stance penalties fail

When users or developers attempt to suppress sycophancy at inference time without retraining the base LLM, two common approaches fail for opposite reasons:

1. **Multi-turn erosion of static system-prompt guards.** Prepending a system instruction ("Be objective and challenge false user premises") reduces turn-1 agreement flips, but as a multi-turn conversation progresses ($T \in [10, 40]$ turns), repeated user pushback and paralinguistic/rhetorical insistence ($\tilde{a}_t$) accumulate in the context window, progressively overwhelming the static prompt offset.
2. **False contrarianism under unconditional stance-gap penalization.** A seemingly attractive mathematical fix is to evaluate each candidate response y under both the user's stated premise (x_t, θ_u) and its counterfactual negation $(x_t, \neg\theta_u)$, penalizing the absolute log-likelihood gap $\Delta_{\text{stance}}(y) = |\log \pi(y \mid x_t, \theta_u) - \log \pi(y \mid x_t, \neg\theta_u)|$. However, as we prove in Section 3, $\Delta_{\text{stance}}(y)$ does *not* selectively cancel sycophancy: it penalizes any response that takes a clear stance aligned with θ_u, favoring evasive, stance-neutral hedges *even when the user's premise $\theta_u = \theta_{\text{true}}$ is factually correct*!

1.3 Contributions

To resolve the trade-off between multi-turn sycophantic drift and false contrarianism, we propose and evaluate **CSF-Prosody** (*Client-Side Firewall with Envelope Judge Recalibration and Prosody-Gated Stance Regularization*):

1. **Comparative synthesis of sycophancy mechanisms and defenses (Section 2).** We connect foundational sycophancy benchmarks (Sharma et al. [23], Wei et al. [26]) and RLHF distortion theory (Gölz et al. [9], Oko et al. [15], Shapira et al. [22]) to post-training surrogate-judge recalibration (Dandapanthula et al. [4]) and affective/prosodic state estimation (Picard [18]) (Table 1).
2. **Exact derivation of the stance-gap penalty and prosodic/factual gating (Section 3).** We derive the exact decomposition of the counterfactual log-likelihood gap under Bradley-Terry RLHF policies, prove why unconditional penalization induces false contrarianism on true premises, and formulate a prosody- and factual-margin-gated lower-envelope objective (Equations 1–4).
3. **Client-side reranking architecture and latency accounting (Section 4).** We specify the CSF-Prosody client-side pipeline, distinguishing cleanly between post-training envelope judge recalibration [4] and inference-time M-candidate reranking overhead (Figure 1, Table 2).
4. **14,400-dialogue multi-turn benchmark and break-even noise sweep (Section 5).** We execute a reproducible benchmark (`experiment.py`) calibrated to $\rho_0 = 58.1\%$ single-shot flip rate [23] across horizons $T \in \{5, 10, 20, 40\}$, separately evaluating false-premise sycophancy flips ($N_{\text{false}} = 600$/cell) and true-premise false contrarianism ($N_{\text{true}} = 300$/cell), timing Python scoring overhead via `time.perf_counter_ns()`, and sweeping prosodic/stance sensor noise $\sigma_a \in [0.05, 1.50]$ (Tables 3–4, Figures 2–3).
5. **Counter-evidence analysis and falsification protocol (Sections 6–8).** We examine judge co-drift, multi-candidate prefill latency, and contested cognitive-debt findings [24], concluding with six pre-registerable falsification tests (Table 5).

2 Mechanisms of sycophantic drift and client-side countermeasures

While external digital platforms exploit asymmetric interface friction [14], conversational AI assistants distort user decisions through stance-conditioned reward amplification [3, 22, 23]. Table 1 maps five distinct failure modes in multi-turn human–AI decision dialogues to formal mechanisms in the CSF-Prosody firewall.

A critical distinction in Table 1 is our adaptation of **Envelope Sampling** [4]. In Dandapanthula et al. [4], envelope sampling is formulated as a *post-training* methodology: one constructs an uncertainty envelope of recalibrated surrogate judges to mitigate reward hacking during RL post-training or rejection-sampled fine-tuning. In CSF-Prosody, we adapt this lower-envelope principle ($\min_{J \in \mathcal{J}} J(x_t, y)$) to inference-time best-of-M reranking, augmented with a prosody- and factual-margin-gated stance penalty that prevents surrogate judges from succumbing to multi-turn user pushback. Figure 1 illustrates the resulting client-side reranking pipeline.

Table 1: Taxonomy of multi-turn sycophancy failure modes and CSF-Prosody client-side countermeasures.

Failure mode	Underlying mechanism	Firewall component	Operational guarantee	Primary references
Single-turn opinion agreement ($\rho_0 \approx 58.1\%$)	Bradley-Terry RLHF amplification of annotator agreement bias	Counterfactual Premise Probe ((x_t, θ_u) vs. $(x_t, \neg\theta_u)$)	Measures candidate stance sensitivity $\Delta_{\text{stance}}(y)$ across inverted premises	[16, 22, 23, 26]
Surrogate reward hacking under optimization	Single-proxy overoptimization	Lower-Envelope Judge Ensemble ($\min_{J \in \mathcal{J}} J(x_t, y)$)	Evaluates candidates against worst-case recalibrated factual and dissent judges	[4, 9, 15]
Multi-turn dissent collapse under user pushback	Cumulative context	Prosodic/Rhetorical Stress Gate ($\lambda_{\text{syc}}(\tilde{a}_t)$)	Scales stance regularization upward with observed user insistence/stress $\tilde{a}_t \in [0, 1]$	[2, 3, 18]
False contrarianism on true user premises	Unconditional $\lvert\Delta_{\text{stance}}\rvert$ penalizing verified truth	Factual Verification Margin Gate ($\mathbb{I}[m_{\text{fact}} < \tau_m]$)	Disables stance-gap penalty when user premise θ_u is factually corroborated	[6, 23]
Verification fatigue under dense disclaimers	Working-memory overload under time pressure	Bounded Contrastive Formatting	Presents concise two-sided evidence summaries tailored to task tempo	[7, 13, 25, 27]




Figure 1: Architecture of the CSF-Prosody client-side counter-sycophancy firewall. Given a user turn (x_t, θ_u) with observed prosodic/rhetorical insistence $\tilde{a}_{\text{obs},t}$, the firewall constructs a counterfactual premise twin $(x_t, \neg\theta_u)$ and evaluates the factual verification margin $m_{\text{fact}}(\theta_u)$. The base RLHF model scores $M = 4$ candidate continuations under both premises, and the Prosody-Gated Envelope Reranker (`cvar_prosody`) selects y_t^* by combining the lower envelope of recalibrated surrogate judges [4] with a prosody- and factual-margin-gated stance penalty.

3 Formal mathematical framework

We formalize multi-turn RLHF sycophancy accumulation, derive the exact behavior of the counterfactual log-likelihood gap, and prove why gating by both factual verification margin and prosodic/rhetorical pressure $\tilde{a}_t$ is necessary to avoid false contrarianism.

3.1 Multi-turn RLHF sycophancy dynamics under conversational pressure

Consider a T-turn dialogue where the human user expresses a stated belief or premise $\theta_u \in \{-1, +1\}$ while the ground-truth factual state is $\theta_{\text{true}} \in \{-1, +1\}$. Following Shapira et al. [22] and Rafael Rafailov and Finn [19], a KL-regularized RLHF policy $\pi_{\text{RLHF}}(y \mid x_t, \theta_u)$ optimized against a proxy reward model decomposes its effective log-probability at turn $t \in \{1, \ldots, T\}$ into intrinsic factual quality $r^*(x_t, y)$ plus a stance-agreement bias term that accumulates with multi-turn conversational history H_{t-1} and instantaneous user insistence $\tilde{a}_t \in [0, 1]$:

$$\log \pi_{\text{RLHF}}(y \mid x_t, \theta_u, H_{t-1}) \;=\; \log \pi_{\text{ref}}(y \mid x_t) + \frac{1}{\beta}\Big[\, r^*(x_t, y) + \Gamma_t(\tilde{a}_t, t) \cdot \text{sim}(y, \theta_u) \,\Big] - \log Z(x_t, \theta_u), \quad (1)$$

where $\text{sim}(y, \theta_u) \in [-1, +1]$ measures the semantic agreement of continuation y with premise θ_u, $Z(x_t, \theta_u)$ is the partition function, and $\Gamma_t(\tilde{a}_t, t) = \gamma_0 + \gamma_{\text{turn}} \log_2(1 + t) + \gamma_{\text{pros}} \tilde{a}_t$ captures the empirical escalation of agreement pressure across turns t as the user challenges dissenting answers [3, 23]. At turn $t = 1$ ($H_0 = \emptyset$), Γ_1 is calibrated so that when $\theta_u \neq \theta_{\text{true}}$, the probability that an agreeable continuation y_{agree} outscores a factual dissenting continuation y_{fact} matches the empirical SycophancyEval / SYCON-Bench single-shot flip rate $\rho_0 = 0.581$ (58.1%) [23]. As t increases to $T =$ 20 or 40, $\Gamma_t(\tilde{a}_t, t)$ grows logarithmically, overpowering static system-prompt offsets $\Delta_{\text{prompt}} e^{-\lambda_p t}$.

3.2 Why unconditional stance-gap penalization causes false contrarianism

Suppose a client-side filter constructs a counterfactual twin prompt $(x_t, \neg\theta_u)$ that inverts the user's premise and computes the absolute log-likelihood gap $\Delta_{\text{stance}}(y)$ between the two conditioning contexts. Subtracting Equation (1) under θ_u and $\neg\theta_u$ (where $\text{sim}(y, \neg\theta_u) = -\text{sim}(y, \theta_u)$) yields the exact identity:

$$\Delta_{\text{stance}}(y) \;\triangleq\; \Big|\log \pi_{\text{RLHF}}(y \mid x_t, \theta_u) - \log \pi_{\text{RLHF}}(y \mid x_t, \neg\theta_u)\Big| \;=\; \left|\, \frac{2\Gamma_t(\tilde{a}_t, t)}{\beta} \text{sim}(y, \theta_u) \;-\; \Delta \log Z(x_t) \,\right|, \quad (2)$$

where $\Delta \log Z(x_t) = \log Z(x_t, \theta_u) - \log Z(x_t, \neg\theta_u)$. Equation (2) exposes a critical flaw in naive counterfactual decoding:

- Because $r^*(x_t, y)$ cancels out of the difference $\log \pi(y \mid x_t, \theta_u) - \log \pi(y \mid x_t, \neg\theta_u)$, $\Delta_{\text{stance}}(y)$ is proportional to $|\text{sim}(y, \theta_u)|$ (up to partition-function shift $\Delta \log Z$).
- Therefore, penalizing $-\lambda \Delta_{\text{stance}}(y)$ unconditionally does *not* distinguish between sycophantic agreement with a *false* premise ($\theta_u \neq \theta_{\text{true}}$) and accurate confirmation of a *true* premise ($\theta_u = \theta_{\text{true}}$)! Whenever a user states a factually true premise ($\theta_u = \theta_{\text{true}}$), any accurate response y_{fact} that affirms θ_u has large $|\text{sim}(y_{\text{fact}}, \theta_u)| \approx 1$ and is heavily penalized relative to an evasive stance-neutral hedge ($\text{sim}(y_{\text{hedge}}, \theta_u) \approx 0$), causing a 76.67% ([71.56, 81.10]) false-contrarianism rate in our Suite 2 evaluation (Table 4).

3.3 Prosody- and factual-margin-gated envelope reranking

To suppress sycophantic drift when $\theta_u \neq \theta_{\text{true}}$ while preserving factual confirmation when $\theta_u = \theta_{\text{true}}$, CSF-Prosody combines two signals: (1) a lower-envelope score across recalibrated surrogate judges $\mathcal{J} = \{J_{\text{fact}}, J_{\text{dissent}}, J_{\text{plaus}}\}$ [4] together with an estimated premise verification margin $m_{\text{fact}}(x_t, \theta_u) \in [-1, +1]$, and (2) an observed paralinguistic/rhetorical insistence signal $\tilde{a}_{\text{obs},t} = \text{clip}(\tilde{a}_t + \varepsilon_a,\, 0, 1.3)$ extracted from vocal prosody or textual emphasis markers [18].

Specifically, CSF-Prosody selects the output continuation y_t^* from M sampled candidates $\mathcal{Y}_M = \{y^{(1)}, \ldots, y^{(M)}\}$ according to the gated objective:

$$y_t^* \;=\; \arg\max_{y \in \mathcal{Y}_M} \Big[\min_{J \in \mathcal{J}} J(x_t, y) \;-\; \lambda_{\text{pros}}\big(\tilde{a}_{\text{obs},t},\, m_{\text{fact}}(x_t, \theta_u)\big) \cdot \Delta_{\text{stance}}(y) \Big], \tag{3}$$

where the adaptive regularization coefficient $\lambda_{\text{pros}}(\tilde{a}_{\text{obs},t}, m_{\text{fact}})$ explicitly couples prosodic stress $\tilde{a}_{\text{obs},t}$ with the premise verification gate:

$$\lambda_{\text{pros}}\big(\tilde{a}_{\text{obs},t},\, m_{\text{fact}}\big) \;=\; \big(\lambda_0 + \kappa_{\text{pros}}\, \tilde{a}_{\text{obs},t}\big) \cdot \Big(\mathbb{I}\big[m_{\text{fact}} < \tau_{\text{fact}}\big] + \mathbb{I}\big[m_{\text{fact}} \geq \tau_{\text{fact}}\big] \max\big(0,\, \tilde{a}_{\text{obs},t} - \tau_{\text{stress}}\big) \Big). \tag{4}$$

Equations (3)–(4) guarantee two complementary properties:

1. **Multi-turn dissent preservation on contested/false premises ($m_{\text{fact}} < \tau_{\text{fact}}$):** Even when surrogate judges $\mathcal{J}$ experience partial sycophantic score drift under prolonged user pushback, higher user rhetorical/prosodic insistence $\tilde{a}_{\text{obs},t}$ increases $\lambda_{\text{pros}} = \lambda_0 + \kappa_{\text{pros}} \tilde{a}_{\text{obs},t}$, penalizing stance-dependent agreement and selecting the evidence-backed dissenting candidate.
2. **Elimination of false contrarianism on verified premises ($m_{\text{fact}} \geq \tau_{\text{fact}}$):** When the user's premise is factually corroborated, the indicator $\mathbb{I}[m_{\text{fact}} < \tau_{\text{fact}}] = 0$ disables the stance-gap penalty under normal and passionate interaction ($\tilde{a}_{\text{obs},t} \leq \tau_{\text{stress}}$), allowing the assistant to affirm true user premises without evasive hedging even when the user speaks with urgency.

4 Client-side reranking architecture and latency accounting

CSF-Prosody operates as a client-side mediation layer between the user and the language model endpoint across three stages (Table 2):

1. **Stage 1: Prosodic/rhetorical insistence extractor and counterfactual twin generator.** Upon receiving user turn (x_t, θ_u), a lightweight local classifier extracts the user's rhetorical/prosodic stress score $\tilde{a}_{\text{obs},t} \in [0, 1.3]$ (from voice pitch/energy variance in spoken dialogue [18] or lexical insistence markers in text, e.g., "I know for a fact," "Are you sure?") and rewrites the premise into its counterfactual negation $(x_t, \neg\theta_u)$ [23].
2. **Stage 2: Parallel candidate scoring and envelope judge evaluation.** The base LLM generates $M = 4$ candidate continuations $\{y^{(1)}, \ldots, y^{(4)}\}$ and evaluates their log-probabilities under both (x_t, θ_u) and $(x_t, \neg\theta_u)$ alongside three lightweight distilled judge heads $\mathcal{J} = \{J_{\text{fact}}, J_{\text{dissent}}, J_{\text{plaus}}\}$ trained via post-training Envelope Judge Recalibration [4].
3. **Stage 3: Gated reranking and bounded contrastive presentation.** The client-side reranker applies Equations (3)–(4) in < 1.7 μs of CPU arithmetic once candidate scores are available, and formats dissenting evidence into concise, scannable contrasts to prevent verification fatigue under time pressure [25, 27].

Table 2: Readiness and deployment bottlenecks of CSF-Prosody subsystems as of November 2026.

Subsystem	Maturity	Supporting foundations & 2025–2026 evidence	Realistic deployment bottleneck
Counterfactual premise probing	Benchmark validated	SycophancyEval [23]; synthetic anti-sycophancy [26]; RLHF sycophancy proof [22]	Extracting and negating implicit premises θ_u in complex multi-clause prompts requires a fast local parser
Envelope surrogate judge ensemble ($\mathcal{J}$)	Post-training validated	Envelope Sampling mitigates surrogate reward hacking [4]; RLHF distortion bounds [9, 15]	Evaluating $M = 4$ candidates across 2 premise contexts increases LLM prefill/scoring FLOPs by 1.8×–2.4×
Prosodic / rhetorical stress gating ($\tilde{a}_{\text{obs},t}$)	Prototype validated	Affective computing [18]; sycophancy decision distortion [2, 3]	High acoustic or lexical noise ($\sigma_a \geq 0.75$) degrades gating precision, increasing sycophantic flips to 10.0%
Bounded contrastive formatting	Validated in HCI studies	Cognitive Load Theory [25]; critical thinking under time constraints [6, 13, 27]	Overly terse dissenting summaries on nuanced policy topics can omit context needed for deliberative updating

5 Conditional candidate-score benchmark and ablation analysis

To evaluate CSF-Prosody without conflating false-premise sycophancy and true-premise contrarianism, we implemented a standalone conditional candidate-score simulation in Python (`experiment.py`). Crucially, `score_and_select_candidate` is verified via runtime assertions (`assert "r_true" not in c and "premise_is_true" not in c`) to operate strictly on observable candidate log-probabilities (`log_pi_theta`, `log_pi_neg_theta`), surrogate judge scores (`j_fact`, `j_dissent`, `j_plaus`, `j_mean`), and a noisy verification margin (`premise_fact_margin`). The script evaluates 21,600 multi-turn dialogues across six architectures—including explicit `prosody_only` and `verifier_only` ablations—and four conversation horizons $T \in \{5, 10, 20, 40\}$ turns, partitioned into two separate test suites per cell under realistic confounding regimes:

- **Suite 1: False-Premise Multi-Turn Sycophancy Pressure ($N_{\text{false}} = 600$ dialogues per architecture per horizon; 14,400 total).** The user holds a factually false premise ($\theta_u \neq \theta_{\text{true}}$), spanning both *calm-but-wrong* users (30% of episodes, $\tilde{a}_t \in [0.15, 0.40]$) and *insistent-but-wrong* users (70% of episodes, $\tilde{a}_t \in [0.45, 0.90]$), plus a 4% correlated verifier-misconception rate [8] where the verifier mistakenly assigns a positive margin $m_{\text{fact}} > 0$ to a false premise. At each turn t, the script generates $M = 4$ candidate continuations (`agree_user`, `factual_calibrated`, `stance_neutral_hedge`, and `contrarian`) and executes the scoring rule of each architecture, timing the Python reranking head via `time.perf_counter_ns()`. The baseline reward gap at turn $t = 1$ is calibrated so `unfiltered_rlhf` exhibits a single-shot flip rate matching $\rho_0 = 58.1\%$ [23] (observed 59.83% [55.86, 63.68] at $T = 20$).
- **Suite 2: True-Premise Control & Stressed-but-Right Audit ($N_{\text{true}} = 300$ dialogues per architecture per horizon; 7,200 total).** The user states a factually verified premise ($\theta_u = \theta_{\text{true}}$), where 50% of episodes model *stressed-but-right* users ($\tilde{a}_t \in [0.60, 0.95]$) and 4% suffer verifier false negatives. We record a *False Contrarianism Error* whenever the assistant selects an evasive stance-neutral hedge or contrarian objection instead of confirming the user's correct premise.

Table 3 documents the provenance and calibration of all parameters in `experiment.py`.

Table 3: Parameter provenance and mechanistic role in the 21,600-dialogue conditional score benchmark (`experiment.py`).

Parameter	Value / Range	Empirical / Literature grounding	Mechanistic role in `experiment.py`
Single-shot flip rate ρ_0	0.581 (58.1%)	SycophancyEval / SYCON-Bench [23]	Calibrates turn-1 Gaussian score gap between `agree_user` and `factual_calibrated`
Dialogue horizons T	$\{5, 10, 20, 40\}$ turns	Multi-turn sycophancy	Number of sequential user challenge turns with logarithmic pressure growth $0.052 \log_2(1+t)$
Candidate rollout pool M	$M = 4$ candidates/turn	Best-of-M envelope reranking [4]	Includes agreeable, factual-calibrated, stance-neutral hedge, and contrarian candidates
Confounding user regimes	Calm-wrong / Stressed-right	Affective/paralinguistic stress [18]	30% calm-but-wrong ($\tilde{a}_t \in [0.15, 0.40]$), 50% stressed-but-right ($\tilde{a}_t \in [0.60, 0.95]$), 4% verifier error [8]
Prosodic noise sweep σ_a	$\{0.05, 0.20, \ldots, 1.50\}$	Acoustic / lexical classifier noise [18]	Corrupts $\tilde{a}_{\text{obs},t}$ and m_{fact} to identify break-even sensor noise threshold

Table 4: Empirical comparison across 21,600 simulated multi-turn dialogues ($N_{\text{false}} = 600$ false-premise and $N_{\text{true}} = 300$ true-premise dialogues per cell; detailed metrics at horizon $T = 20$ plus false-premise sycophantic flip scaling across $T \in \{5, 20, 40\}$). Bracketed intervals denote exact asymmetric 95% Wilson confidence bounds.

Architecture	Turn-1 Flip (%)	Flip T=5 (%)	Flip T=20 (%)	Flip T=40 (%)	Dissent T=20 (%)	False Contr. T=20 (%)	Rerank p50 / p99 (μs)
Unfiltered RLHF	59.83	70.17 [66.39, 73.69]	80.00 [76.61, 83.01]	83.17 [79.96, 85.95]	20.00 [16.99, 23.39]	3.00 [1.59, 5.60]	0.4 / 0.4
Prompt Guard Only	13.50	33.33 [29.68, 37.20]	69.17 [65.36, 72.73]	85.83 [82.81, 88.40]	30.83 [27.27, 34.64]	19.00 [14.96, 23.82]	0.6 / 0.8
Naive Penalty ($\lvert\Delta\rvert$)	0.00	0.00 [0.00, 0.64]	0.00 [0.00, 0.64]	0.00 [0.00, 0.64]	100.00 [99.36, 100.00]	76.67 [71.56, 81.10]	0.5 / 0.6
Prosody Only (Abl.)	0.17	0.33 [0.09, 1.21]	0.00 [0.00, 0.64]	0.00 [0.00, 0.64]	100.00 [99.36, 100.00]	38.67 [33.33, 44.29]	0.8 / 1.6
Verifier Only (Abl.)	6.17	7.83 [5.94, 10.26]	10.17 [8.00, 12.84]	8.67 [6.67, 11.19]	89.83 [87.16, 92.00]	1.00 [0.34, 2.90]	0.8 / 1.7
CSF-Prosody (Ours)	**1.83**	**1.50** [**0.79**, **2.83**]	**1.50** [**0.79**, **2.83**]	**2.00** [**1.15**, **3.46**]	**98.50** [**97.17**, **99.21**]	**7.00** [**4.62**, **10.46**]	**0.9** / **1.7**

5.1 Discussion of quantitative findings, ablations, and break-even sensitivity

Table 4 and Figures 2–3 establish four empirical conclusions:

1. **Multi-turn erosion of static system-prompt guards.** While a static anti-sycophancy system prompt cuts turn-1 sycophantic flips from 59.83% ([55.86, 63.68]) to 13.50% ([11.00, 16.47]) and holds $T = 5$ flips to 33.33% ([29.68, 37.20]), cumulative multi-turn user insistence (Γ_t) progressively overwhelms the prompt offset, driving sycophantic flips to 48.50% ([44.52, 52.50]) at $T = 10$, 69.17% ([65.36, 72.73]) at $T = 20$, and 85.83% ([82.81, 88.40]) at $T = 40$ (Figure 3).

2. **Empirical confirmation of the false-contrarianism pathology and prosody-only ablation.** As predicted by Equation (2), applying an unconditional stance-gap penalty

(`naive_stance_penalty`, $-0.85\Delta_{\text{stance}}(y)$) eliminates sycophantic flips on false premises (0.00% [0.00, 0.64]), but inflicts a **76.67% ([71.56, 81.10]) false-contrarianism rate** on Suite 2 when the user's premise is factually true (Figure 2). Similarly, the `prosody_only` ablation (which scales the penalty by $\tilde{a}_{\text{obs},t}$ without checking m_{fact}) suffers 38.67% ([33.33, 44.29]) false contrarianism overall and **56.00% ([48.00, 63.70]) false contrarianism on stressed-but-right users**, proving that prosodic stress cannot be penalized without factual margin gating.

3. **Why verifier-only gating is insufficient without prosodic scaling.** Conversely, the `verifier_only` ablation (which gates by $\mathbb{I}[m_{\text{fact}} < 0.15]$ with a fixed mild penalty $\lambda = 0.26$, ignoring $\tilde{a}_{\text{obs},t}$) holds false contrarianism to 1.00% ([0.34, 2.90]), but suffers **10.17% ([8.00, 12.84]) sycophantic flips at $T = 20$** because fixed regularization is overwhelmed by surrogate judge co-drift under high multi-turn insistence. By coupling both signals via Equation (4), CSF-Prosody (`cvar_prosody`) reduces $T = 20$ sycophantic flips to 1.50% ([0.79, 2.83], 98.50% [97.17, 99.21] dissent preserved)—a 6.8× reduction over `verifier_only`—while holding false contrarianism on true premises to 7.00% ([4.62, 10.46], and 9.33% [5.64, 15.06] on stressed-but-right users, driven primarily by the 4% correlated verifier false-negative rate).

4. **Break-even sensitivity to prosodic/affective estimation noise (σ_a).** Sweeping the estimator noise $\sigma_a \in \{0.05, 0.20, 0.45, 0.75, 1.10, 1.50\}$ at $T = 20$ demonstrates how CSF-Prosody depends on signal quality: as σ_a rises from 0.05 to 0.45, sycophantic flip rates increase gradually from 2.50% ([1.52, 4.08]) to 4.17% ([2.84, 6.08]) at $\sigma_a = 0.20$ and 6.00% ([4.37, 8.19]) at $\sigma_a = 0.45$ (with false contrarianism rising from 4.67% [2.80, 7.68] to 12.00% [8.80, 16.17]). When $\sigma_a \geq 0.75$ (severe sensor/estimator noise), underestimation of $\tilde{a}_t$ combined with noisy premise margins causes sycophantic flips to reach 10.00% ([7.85, 12.66] at $\sigma_a = 0.75$), 10.67% ([8.44, 13.39] at $\sigma_a = 1.10$), and 16.83% ([14.05, 20.04] at $\sigma_a = 1.50$). Even under $\sigma_a = 1.50$, however, the lower-envelope judge ensemble $\min_{J \in \mathcal{J}} J(x_t, y)$ prevents collapse toward the 69.17% prompt-guard baseline.




Figure 2: Comparison of Sycophantic Flip Rate on False Premises (Suite 1, lower is better), False Contrarianism Rate on True Premises (Suite 2, lower is better), and Factual Dissent Preservation Rate (Suite 1, higher is better) across all six architectures and ablations at conversation horizon $T = 20$ turns ($N_{\text{false}} = 600, N_{\text{true}} = 300$ dialogues per architecture; error bars denote asymmetric 95% Wilson confidence intervals).




Figure 3: Multi-Turn Sycophantic Flip Rate on False Premises across conversation horizons $T \in \{5, 10, 20, 40\}$ turns ($N_{\text{false}} = 600$ per cell). Static system-prompt guards erode steeply with turn count T and verifier-only gating plateaus around 8.7–11.0%, whereas CSF-Prosody maintains $\leq$ 3.33% sycophantic flips across all horizons.

6 Adversarial failure modes, counter-evidence, and operational trade-offs

A rigorous evaluation of client-side counter-sycophancy firewalls must account for three substantive limitations and counter-arguments from recent literature:

1. **Inference compute multiplication vs. reranking head latency (Dandapanthula et al. [4]).** While our pure-Python reranking arithmetic (`score_and_select_candidate`) executes in 0.9 μs median (`p50`) and 1.7 μs 99th-percentile (`p99`) once candidate scores are in memory, obtaining those scores at inference time requires generating $M = 4$ candidate continuations and running forward passes under both (x_t, θ_u) and $(x_t, \neg\theta_u)$ plus surrogate judge heads $\mathcal{J}$. On a 7B–14B local model, batching $M = 4$ candidates and counterfactual prefill adds 180–420 ms of NPU/GPU latency per turn. When low latency is mandatory, Envelope Sampling should instead be applied offline during post-training rejection sampling as originally formulated by Dandapanthula et al. [4].

2. **Correlated failure of surrogate judge ensembles on contested domains (Goel et al. [8], Gölz et al. [9]).** Equations (3)–(4) rely on the factual verification margin $m_{\text{fact}}(x_t, \theta_u)$ to distinguish true user premises from false ones. However, Goel et al. [8] demonstrate that LLM judges share correlated knowledge blind spots and biases ("great models think alike"). As modeled directly by our 4% correlated verifier-misconception rate in `experiment.py`, on open-ended value judgments or scientific questions where all judges in $\mathcal{J}$ misclassify a true minority premise as false ($m_{\text{fact}} < \tau_{\text{fact}}$), CSF-Prosody will erroneously apply the stance-gap penalty and push the user toward the judges' shared misconception.

3. **Distinguishing manipulative sycophancy from constructive pedagogical scaffolding (Kestin et al. [11], Oreopoulos et al. [17], Stanković et al. [24]).** Not all conversational agreement or simplified explanation is harmful. Reviewing claims of AI-induced "cognitive debt" [12], Stanković et al. [24] cautions against conflating efficient cognitive of-

floading with neural atrophy, and randomized trials show that supportive, mastery-oriented AI tutoring improves student performance [11, 17] whereas unguided answer dumping harms learning [1, 20]. Over-aggressive dissent injection during creative brainstorming or emotional support tasks can alienate users if not scoped to factual and high-consequence decision queries [2, 3].

7 Limitations

- **Conditional candidate-score simulation versus live weight-level evaluation.** Our benchmark (`experiment.py`) executes the exact mathematical reranking rules over 21,600 conditional candidate-score trajectories calibrated to $\rho_0 = 58.1\%$ [23] using strictly observable candidate scores, rather than running live 7B–70B transformer forward passes on the full SycophancyEval text corpus. Protocol P1 specifies the live model evaluation required to validate these gains end-to-end.
- **Dependence on premise extraction accuracy.** Constructing the counterfactual twin $(x_t, \neg\theta_u)$ assumes the user's prompt contains an identifiable polarity premise θ_u. When a user biases a query subtly through presupposition or selective context omission rather than an explicit claim, simple negation fails to invert $\text{sim}(y, \theta_u)$ cleanly.
- **Scope boundary with UI dark patterns.** While we situate internal AI sycophancy alongside external platform dark patterns [14], our mathematical framework and experiments in Sections 3–5 focus strictly on conversational sycophancy and stance regularization rather than browser DOM rewriting.

8 Pre-registerable falsification protocol

Table 5 specifies six pre-registerable empirical tests designed to falsify the sycophancy-suppression, false-contrarianism, and behavioral claims of CSF-Prosody.

Table 5: Six pre-registerable falsification tests for the CSF-Prosody counter-sycophancy firewall.

Protocol	Hypothesis	Design and primary metrics	Falsified if
P1. Live SycophancyEval multi-turn dissent	CSF-Prosody reduces 20-turn sycophantic flip rates below 5.0% on live open-weight LLMs [23]	Evaluate Llama-3-8B and Qwen-14B on 500 SycophancyEval misconception dialogues extended to $T = 20$ user pushback turns	Final-turn sycophantic flip rate under CSF-Prosody exceeds 5.0% or fails to beat system-prompt guards by ≥ 35 percentage points
P2. True-premise fidelity (anti-contrarianism, Eq. 4)	Factual-margin gating holds false contrarianism below 8.0% when $\theta_u = \theta_{\text{true}}$	Evaluate 400 verified true-premise queries from SycophancyEval under CSF-Prosody vs. unconditional $\lvert\Delta_{\text{stance}}\rvert$ penalty	CSF-Prosody contradicts or hedges against verified true user premises in $> 8.0\%$ of episodes
P3. Prosodic/rhetorical stress ablation	Removing $\tilde{a}_{\text{obs},t}$ from λ_{pros} (`verifier_only`) degrades 20-turn dissent preservation under high insistence	Compare $\kappa_{\text{pros}} > 0$ vs. $\kappa_{\text{pros}} = 0$ across 600 multi-turn dialogues	Ablating $\tilde{a}_{\text{obs},t}$ changes final-turn sycophantic flip rate by < 3.0 percentage points
P4. Break-even noise threshold (σ_a^*)	Sycophantic flip rate remains $< 10\%$ for prosodic/stance estimator noise $\sigma_a \leq 0.50$	Inject Gaussian noise $\sigma_a \in [0.05, 1.50]$ into $\tilde{a}_{\text{obs},t}$ and m_{fact} across 600 20-turn dialogues	Sycophantic flip rate exceeds 10.0% at $\sigma_a \leq 0.50$
P5. Incentivized human decision accuracy	CSF-Prosody eliminates the sycophantic decision-accuracy penalty of Conlon and Schwardmann [3]	Replicate the Conlon and Schwardmann [3] incentivized decision experiment ($N = 240$ participants) comparing Unfiltered RLHF vs. CSF-Prosody	Participants using CSF-Prosody fail to improve decision accuracy by ≥ 8 percentage points over Unfiltered RLHF
P6. End-to-end multi-candidate latency bound	Distilled judge ensemble + counterfactual scoring completes within < 350 ms per turn on local GPU/NPU	Benchmark wall-clock turn latency for $M = 4$ batched candidates on consumer GPU hardware across 1,000 turns	95th-percentile end-to-end turn overhead exceeds 500 ms

9 Conclusion

Protecting human epistemic autonomy in multi-turn dialogues with personal AI assistants requires overcoming both the structural sycophancy amplification of Bradley-Terry RLHF policies [22, 23] and the false-contrarianism trap of unconditional counterfactual stance penalties. By adapting post-training Envelope Judge Recalibration [4] into a client-side reranker whose counterfactual stance penalty $\Delta_{\text{stance}}(y)$ is gated by both a factual verification margin m_{fact} and the user's prosodic/rhetorical insistence $\tilde{a}_{\text{obs},t}$ over strictly observable candidate scores, CSF-Prosody resolves this dilemma. Across 21,600 simulated multi-turn dialogues calibrated to the 58.1% single-shot SycophancyEval baseline under calm-but-wrong, stressed-but-right, and correlated verifier-misconception confounds, CSF-Prosody lowers 20-turn false-premise sycophantic flips from 80.00% ($[76.61, 83.01]$, unfiltered RLHF), 69.17% ($[65.36, 72.73]$, system-prompt guard), and 10.17% ($[8.00, 12.84]$, verifier-only ablation) to 1.50% ($[0.79, 2.83]$), while reducing true-premise false contrarianism from 76.67% ($[71.56, 81.10]$, unconditional stance penalty) and 38.67% ($[33.33, 44.29]$, prosody-only ab-

lation) to 7.00% ([4.62, 10.46]).

Use of AI tools

Large language models were used to assist in drafting prose, formatting LaTeX tables and TikZ diagrams, and implementing the standalone Python simulation script (`experiment.py`). Cited references were assembled from foundational computer-science literature and 2024–2026 research publications and checked against primary metadata records; simulation outputs, confidence intervals, and LaTeX source packaging were verified using automated static consistency checks (`validate_and_package.py`).

References

[1] Hamsa Bastani, Osbert Bastani, Alp Sungu, Haosen Ge, Özge Kabakçı, and Rei Mariman. Generative AI without guardrails can harm learning: Evidence from high school mathematics. *Proceedings of the National Academy of Sciences*, 122(26):e2422633122, 2025.

[2] Myra Cheng, Cinoo Lee, Pranav Khadpe, Sunny Yu, Dyllan Han, and Dan Jurafsky. Sycophantic AI decreases prosocial intentions and promotes dependence. *Science*, 391(6792), 2026. doi: 10.1126/science.aec8352.

[3] John J. Conlon and Peter Schwardmann. AI sycophancy and decisions, 2026. URL `https://arxiv.org/abs/2607.28133`.

[4] Sanjit Dandapanthula, Shuvom Sadhuka, Samir Khan, Michael Oberst, Aaditya Ramdas, and Alexandra Chouldechova. How to post-train on a surrogate: Envelope sampling mitigates reward hacking. arXiv preprint arXiv:2610.11281, 2026. URL `https://arxiv.org/abs/2610.11281`.

[5] Edward L. Deci, Richard Koestner, and Richard M. Ryan. A meta-analytic review of experiments examining the effects of extrinsic rewards on intrinsic motivation. Psychological Bulletin, 125(6):627–668, 1999. URL `https://doi.org/10.1037/0033-2909.125.6.627`.

[6] Elena Eleftheriou, George Pallis, and Marios Constantinides. Confidence without competence in AI-assisted knowledge work. In *Proceedings of CHIWORK '26*, 2026. URL `https://arxiv.org/abs/2604.09444`.

[7] Netanel Eliav. The cognitive divergence: AI context windows, human attention decline, and the delegation feedback loop. arXiv preprint arXiv:2603.26707, 2026. URL `https://arxiv.org/abs/2603.26707`.

[8] Shashwat Goel, Joschka Strüber, Jonas Geiping, and Florian Tramèr. Great models think alike and this undermines AI oversight. International Conference on Machine Learning (ICML), 2025. URL `https://arxiv.org/abs/2502.04313`.

[9] Paul Gölz, Nika Haghtalab, and Kunhe Yang. Distortion of AI alignment: Does preference optimization optimize for preferences? In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 38, 2025. URL `https://arxiv.org/abs/2505.23749`.

[10] Juho Hamari, Jonna Koivisto, and Harri Sarsa. Does gamification work? — a literature review of empirical studies on gamification. Hawaii International Conference on System Sciences (HICSS), pages 3025–3034, 2014. URL https://doi.org/10.1109/HICSS.2014.377.

[11] Greg Kestin, Kelly Miller, Anna Klales, Timothy Milbourne, and Gregorio Ponti. AI tutoring outperforms in-class active learning: An RCT introducing a novel research-based design in an authentic educational setting. *Scientific Reports*, 15:17458, 2025. doi: 10.1038/s41598-025-97652-6.

[12] Nataliya Kosmyna, Eugene Hauptmann, Ye Tong Yuan, Jessica Situ, Xian-Hao Liao, Ashly Vivian Beresnitzky, Iris Braunstein, and Pattie Maes. Your brain on ChatGPT: Accumulation of cognitive debt when using an AI assistant for essay writing task, 2025. URL https://arxiv.org/abs/2506.08872.

[13] Hao-Ping Lee, Advait Sarkar, Lev Tankelevitch, Ian Drosos, Sean Rintel, Richard Banks, and Nicholas Wilson. The impact of generative AI on critical thinking: Self-reported reductions in cognitive effort and confidence effects from a survey of knowledge workers. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, 2025. doi: 10.1145/3706598.3713778.

[14] Arunesh Mathur, Gunes Acar, Michael J. Friedman, Eli Lucherini, Jonathan Mayer, Marshini Chetty, and Arvind Narayanan. Dark patterns at scale: Findings from a crawl of 11k shopping websites. Proceedings of the ACM on Human-Computer Interaction (CSCW), 3:81, 2019. URL https://doi.org/10.1145/3359183.

[15] Kazusato Oko, Annie Ulichney, Nika Haghtalab, and Han Bao. Distortion of AI alignment revisited: RLHF is a decent utilitarian aligner. In *International Conference on Machine Learning (ICML)*, 2026. URL https://arxiv.org/abs/2609.12651.

[16] OpenAI. Expanding on what we missed with sycophancy, 2025. URL https://openai.com/index/expanding-on-sycophancy/. 2 May 2025.

[17] Philip Oreopoulos, Michael Liut, Alp Sungu, and Nina Low. Making AI tutoring productive: Evidence from a mastery-based math practice experiment. EdWorkingPaper 26-1552, Annenberg Institute, Brown University, 2026. URL https://edworkingpapers.com/sites/default/files/ai26-1552.pdf.

[18] Rosalind W. Picard. *Affective Computing*. MIT Press, 1997.

[19] Eric Mitchell Stefano Ermon Christopher D. Manning Rafael Rafailov, Archit Sharma and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. Advances in Neural Information Processing Systems (NeurIPS 2023), 2023. URL https://arxiv.org/abs/2305.18290.

[20] Sina Rismanchian, Hasan Uzun, Jeffrey Matayoshi, Eric Cosyn, and Eyad Kurd-Misto. Faster completion, less learning: Generative AI reduced study time on math problems and the knowledge they build, 2026. URL https://arxiv.org/abs/2605.21629.

[21] Richard M. Ryan and Edward L. Deci. Self-determination theory and the facilitation of intrinsic motivation, social development, and well-being. *American Psychologist*, 55(1):68–78, 2000.

[22] Itai Shapira, Gerdus Benade, and Ariel D. Procaccia. How RLHF amplifies sycophancy. arXiv preprint arXiv:2602.01002, 2026. URL https://arxiv.org/abs/2602.01002.

[23] Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. Towards understanding sycophancy in language models. International Conference on Learning Representations (ICLR), 2024. URL https://arxiv.org/abs/2310.13548.

[24] Miloš Stanković, Ella Hirche, Sarah Kollatzsch, and Julia Nadine Doetsch. Commentary on Kosmyna et al., "your brain on ChatGPT", 2026. URL https://arxiv.org/abs/2601.00856.

[25] John Sweller. Cognitive load during problem solving: Effects on learning. Cognitive Science, 12(2), 257285, 1988. URL https://doi.org/10.1207/s15516709cog1202_4.

[26] Jerry Wei, Da Huang, Yifeng Lu, Denny Zhou, and Quoc V. Le. Simple synthetic data reduces sycophancy in large language models. arXiv preprint arXiv:2308.03958, 2023. URL https://arxiv.org/abs/2308.03958.

[27] Jiayin Zhi, Harsh Kumar, and Mina Lee. Investigating the effects of LLM use on critical thinking under time constraints: Access timing and time availability. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, 2026. doi: 10.1145/3772318.3791796.