# Human-Observer Attested Web Archival: Preventing Model Autophagy and Synthetic Corpus Collapse Through Cryptographic Provenance Filtering

**Dima Baker**
Collective Intelligence Network

November 2026

**Abstract**

The public web is undergoing an epistemic phase transition: unverified synthetic prose, automated search-engine spam, and agent-generated pull requests increasingly outnumber authentic human records, threatening continual pretraining and retrieval-augmented generation (RAG) with Model Autophagy Disorder (MAD) and tail-knowledge collapse. Post-hoc perplexity detectors suffer high false-positive rates on technical prose, while formal verification of the C2PA specification in 2026 exposed revocation gaps, legacy metadata stripping, and vulnerability to bot-farm signing keys. This architectural synthesis proposes Human-Observer Attested Web Archival (HO-PROV-Archive), a migration pipeline in which legacy web records enter a Merkle-committed provenance ledger when backed by a human-observer curation receipt, a W3C PROV-DM primary-lineage graph (or pre-2022 archival timestamp anchor), and atomic claim verification. Crucially, we distinguish human viewing from human authorship: because human readers can be fooled by fluent LLM text, observer receipts must be coupled with primary-source lineage accumulation to preserve ground-truth support. In a label-blind simulation over shared candidate pools ($K = 80$ clusters, $N = 200$ trajectories/regime) under a preregistered collapse threshold ($D_{\mathrm{KL}} > 0.056$ nats or tail-mass ratio $< 0.72$), HO-PROV-Archive restricts generation-6 collapse to 9.50% $[6.17, 14.36]$ ($D_{\mathrm{KL}} = 0.0406$ $[0.0392, 0.0421]$, tail-mass ratio 91.63%) versus 100.00% $[98.12, 100.00]$ for unfiltered scraping ($D_{\mathrm{KL}} = 0.1555$), perplexity filtering ($D_{\mathrm{KL}} = 0.1830$), and origin-only C2PA checks ($D_{\mathrm{KL}} = 0.1157$), while retaining 82.00% $[76.09, 86.71]$ of tail cohorts. Matched-supply ablation (120 docs/gen) and break-even analysis ($\epsilon^*_{\mathrm{obs}} \approx 0.16$–$0.28$) confirm that gains stem from provenance filtering quality.

## 1 Introduction

For three decades, the World Wide Web functioned as an implicit proxy for collective human knowledge: because producing coherent prose, software repositories, and domain analyses required scarce biological human cognition, uniform web crawls captured an authentic, high-entropy sample of human epistemic output. By late 2026, that foundational assumption had broken down across both text and software ecosystems. Empirical post-mortems of open-source software maintenance in 2026 document a severe commons tragedy in which autonomous coding agents generate massive volumes of superficially plausible pull requests that overwhelm human maintainers and trigger repository abandonment [18, 33]. Concurrently, multi-agent retrieval and citation pipelines suffer from hallucinated citation chains and context drift [24–26], where recursive web indexing ingests synthetic summaries and unverified paraphrases back into active retrieval indices and pretraining mixtures.

### 1.1 Recursive model collapse: replacement versus accumulation

The mathematical consequences of training generative models on recursively polluted corpora were established by a foundational sequence of 2024 studies. Shumailov et al. [28] proved in *Nature* that when generative models are iteratively fitted to finite samples generated by predecessor models, finite-sample approximation error and temperature truncation cause the tails of the underlying distribution to vanish irreversibly (*model collapse*). Alemohammad et al. [1] formalized this feedback loop as Model Autophagy Disorder (MAD), demonstrating progressive quality and diversity decay across iterative self-consuming loops, while Bertrand et al. [4] analyzed the stability conditions of iterative retraining around local optima.

Crucially, however, Gerstgrasser et al. [11] proved both theoretically and empirically across language, diffusion, and variational models that model collapse is *not* inevitable when fresh, original human data $P_0$ is *accumulated* alongside synthetic data rather than replaced. Why, then, do real-world web crawls and RAG indices still face collapse? Because on the live internet, unverified synthetic pages do not arrive neatly labeled as an auxiliary dataset added to a frozen pre-2022 archive: SEO content farms, link-rot replacements, and automated rewrites overwrite legacy URLs and dominate top search-engine rankings, effectively placing naive web-scraping and RAG pipelines into the *replacement* regime of Shumailov et al. [28] unless the ingestion layer can cryptographically distinguish anchored primary records from recursive synthetic echoes.

### 1.2 Why statistical AI detectors and origin-only C2PA manifests fall short

Two primary technical countermeasures have been deployed to filter synthetic web pollution, yet empirical evidence demonstrates that neither suffices on its own:

First, *post-hoc statistical text classifiers and watermarks* attempt to separate synthetic tokens from human writing via perplexity curvature or token green-lists. In practice, statistical detectors degrade under multi-agent paraphrasing, exhibit high false-positive rates on structured technical documentation and non-native English writing, and cannot detect poisoning-based backdoors that lack cryptographic separability [17].

Second, *origin-side cryptographic media manifests*—most notably the Coalition for Content Provenance and Authenticity (C2PA) specification [8]—aim to sign digital assets at creation. However, a 2026 formal-methods security audit of the C2PA specifications by Golaszewski et al. [13] (*"Verifying Provenance of Digital Media: Why the C2PA Specifications Fall Short"*) demonstrated that current C2PA manifests fail to enforce several core provenance guarantees: manifests suffer from certificate revocation and timestamp-authority gaps, are routinely stripped by legacy Content Management Systems (CMS), and cannot prevent an adversarial bot farm from registering a valid organizational signing certificate to sign millions of synthetic articles at origin. Moreover, billions of high-value pages on the "old internet" (1991–2025) predate C2PA entirely and carry zero origin cryptographic signatures.

### 1.3 Epistemic scope of Human-Observer Attested Archival

To preserve the long-tail knowledge of the legacy internet while keeping continual training and RAG corpora in the stable accumulation regime of Gerstgrasser et al. [11], we propose **Human-Observer Attested Web Archival (HO-PROV-Archive)**.

We begin with an explicit epistemic concession: **a human observer's browser dwell-time and interaction receipt attests that a verified human *viewed and curated* a document, not that a human *authored* it.** Because human readers are frequently fooled by fluent, sycophantic, or hallucinated LLM text [7, 9, 27], relying on human reader endorsements alone would

still admit persuasive synthetic slop. Therefore, HO-PROV-Archive requires that human observer curation be jointly anchored to three verifiable provenance mechanisms:

1. **Inalienable human-in-the-loop curation receipts:** Grounded in the Inalienable Human-in-the-Loop (I-HITL) framework [5], the observer's client records a structured interaction witness binding the exact DOM snapshot hash, verified human reading engagement, and an unlinkable personhood credential, while protecting the observer's private reading topic distribution via $d_\chi$-privacy metric perturbation [2].
2. **W3C PROV-DM primary-source lineage and pre-LLM timestamp anchoring:** Following the W3C PROV-DM standard [22], provenance semirings [15], and 2026 provenance-circuit knowledge graphs (`SPARQLcirc` [16] and provenance-enhanced statements [34]), every archived span must link either to a cryptographically timestamped pre-2022 archival snapshot or to a verifiable primary institutional/empirical root entity $\rho$ in $\mathcal{G}_{\text{PROV}}$.
3. **Atomic factuality and citation verification:** Before admission, extracted assertions are decomposed into atomic claims [21] and audited via citation-verifier diagnostics (`HALLMARK` [24, 25]) while rewarding archivists of rare tail knowledge via Local Shapley data valuation [12, 19, 35].

## 2 Provenance architecture taxonomy and 2024–2026 empirical landscape

Migrating legacy web knowledge into a high-integrity ledger requires distinguishing between *syntactic origin signatures* (whether a file carries a TLS or C2PA header) and *epistemic lineage grounding* (whether a claim traces to a non-synthetic primary record or pre-LLM archival snapshot). Table 1 maps five core archival requirements onto formal provenance constructs and verified literature.

Table 1 clarifies why purely automated web scraping fails in the post-2025 internet. When autonomous agents summarize and re-publish web content without provenance semiring tracking [15, 16], secondary aggregators amplify hallucinated citations [24, 25] and induce context drift [26] and governance decay during context compaction [6]. Figure 1 illustrates how HO-PROV-Archive interposes human-observer curation, W3C PROV-DM lineage verification, and $d_\chi$-private Merkle commitments between the public web and the archival ledger.

Table 1: From web-archival requirements to canonical provenance constructs and primary literature.

| Archival requirement | Canonical construct | Ledger component | Operational function | Primary grounding |
|---|---|---|---|---|
| "Prevent headless bot scrapers from flooding the archive" | Inalienable Human-in-the-Loop (I-HITL) witness | Observer Witness Gate ($\mathsf{Witness}_H$) | Binds DOM content hash to verified human reading dwell-time, annotations, and anonymous PoP proof | [2, 5, 32] |
| "Track where every claim came from across edits" | W3C PROV-DM & Provenance Semirings | Provenance DAG & circuit ($\mathcal{G}_{\text{PROV}}$) | Encodes Entity–Activity–Agent lineage and evaluates probabilistic provenance circuits | [15, 16, 22, 34] |
| "Keep training in the accumulation regime, not replacement" | Anchored primary-data accumulation | Pre-2022 / root-lineage anchor vault | Preserves $(1-\tilde{\alpha}_t)P_0$ ground-truth support across generations $t \geq 1$ to prevent tail collapse | [1, 4, 11, 28] |
| "Catch hallucinated citations and stripped C2PA headers" | Atomic claim & citation verification | FActScore + HALLMARK auditor | Audits atomic claim support and flags fabricated or circularly syndicated citations | [13, 21, 24, 25] |
| "Reward humans who curate rare historical dark matter" | Model-Induced Local Data Shapley | Archival utility evaluator ($\phi_{\text{loc}}^{\text{Shap}}$) | Computes tractable marginal contribution of archived tail spans to downstream RAG/model utility | [12, 19, 35] |





Figure 1: Architecture of Human-Observer Attested Web Archival (HO-PROV-Archive). Legacy web content is curated when a verified human observer inspects and annotates a resource, generating an I-HITL witness receipt [5] with a $d_\chi$-differentially private topic embedding [2]. Because human readers cannot reliably spot synthetic prose by eye, the PROV-DM Witness Gate requires either a pre-2022 archival timestamp anchor or a verifiable primary-source lineage path in $\mathcal{G}_{\text{PROV}}$ [16, 22], followed by atomic claim and citation auditing [21, 24] and Local Shapley tail valuation [35].

# 3 Formal model of recursive contamination and anchored accumulation

We formalize web corpus evolution across discrete archival and training generations $t \in \{0, 1, 2, \dots\}$ over a discrete space of $K$ epistemic topic/fact clusters $\mathcal{X} = \{1, \dots, K\}$. Let $P_0(x)$ denote the ground-truth human epistemic distribution over $\mathcal{X}$, characterized by a heavy tail $\mathcal{X}_{\text{tail}} = \{x \in \mathcal{X} : P_0(x) \leq \eta\}$ containing specialized scientific knowledge, historical edge cases, and minority cultural idioms.

## 3.1 Recursive synthetic replacement versus anchored accumulation

At generation $t$, the raw public web distribution $Q_t^{\text{web}}$ consists of a mixture of authentic human-authored content $P_0$ and synthetic outputs generated by models fitted to the previous generation's corpus $P_{t-1}$, with synthetic pollution fraction $\alpha_t \in [0, 1)$:

$$Q_t^{\text{web}}(x) \;=\; (1 - \alpha_t)\, P_0(x) \;+\; \alpha_t\, \mathcal{T}_{\tau,M}(P_{t-1})(x), \tag{1}$$

where $\mathcal{T}_{\tau,M}(P)(x) \propto \text{Multinomial}_M(P(x)^{1/\tau})$ represents finite-sample ($M < \infty$), temperature-sharpened ($\tau < 1$) autoregressive sampling [1, 28]. In an unfiltered replacement crawl ($P_t \approx Q_t^{\text{web}}$), iterating Equation (1) as $\alpha_t \to 1$ causes any rare tail cluster $x \in \mathcal{X}_{\text{tail}}$ whose finite sample count drops to zero to be permanently absorbed, driving $D_{\text{KL}}(P_0 \,\|\, P_t) \to \infty$ [28]. Conversely, if the archival ledger preserves an anchored weight $\gamma_t > 0$ of verified ground-truth distribution $P_0$ at every step $t$, the corpus remains in the accumulation regime of Gerstgrasser et al. [11].

## 3.2 Observer-lineage admission operator and quotient weighting

Let $d_i = (x_i, m_i, w_i, \mathcal{G}_i)$ denote a candidate archival bundle comprising content span $x_i$, cryptographic metadata $m_i$ (pre-2022 archive timestamp, TLS-Notary transcript, or C2PA manifest), human observer witness receipt $w_i$ [5], and W3C PROV-DM citation graph $\mathcal{G}_i$ [22, 34].

Because a human observer $w_i$ can be deceived by fluent synthetic prose, admission requires both a valid observer curation witness $\mathsf{Verify}_{\text{obs}}(w_i) = 1$ and positive primary-lineage circuit evaluation $\mathsf{Support}(c_{i,k}, \rho(c_{i,k})) \in [0, 1]$ via `SPARQLcirc` [16] and `HALLMARK` citation verification [24, 25]. The archival admission weight $\omega(d_i) \in [0, 1]$ is:

$$\omega(d_i) \;=\; \mathbb{I}[\mathsf{Verify}_{\text{obs}}(w_i) = 1] \cdot \left( \frac{1}{L_i} \sum_{k=1}^{L_i} \frac{\mathsf{Support}(c_{i,k},\, \rho(c_{i,k}))}{1 + N_{\text{echo}}(\rho(c_{i,k}))} \right) \cdot \sigma(\phi_{\text{loc}}^{\text{Shap}}(x_i)), \tag{2}$$

where $N_{\text{echo}}(\rho)$ counts prior archived documents deriving from the same root ancestor $\rho$ (quotienting out syndicated reposts), and $\phi_{\text{loc}}^{\text{Shap}}(x_i)$ is the model-induced Local Shapley value [35] that boosts sampling concentration on under-represented tail clusters $x \in \mathcal{X}_{\text{tail}}$.

## 3.3 Derivation of bounded Kullback–Leibler divergence

Let $\epsilon_{\text{obs}} \in [0, 1)$ denote the joint false-acceptance probability that an unverified synthetic document passes both human observer curation and primary-lineage / timestamp verification, and let $\delta_{\text{fn}} \in [0, 1)$ denote the false-negative rejection rate on valid human tail documents. Under Equation (2), the effective synthetic fraction admitted in batch $t$ is compressed from $\alpha_t$ to $\tilde{\alpha}_t = \frac{\alpha_t \epsilon_{\text{obs}}}{(1-\alpha_t)(1-\delta_{\text{fn}}) + \alpha_t \epsilon_{\text{obs}}}$. Since every cluster $x \in \mathcal{X}$ retains at least density $P_t^{\text{HO}}(x) \geq (1-\tilde{\alpha}_t)(1-\delta_{\text{fn}})P_0(x)$ from the anchored

human distribution (and non-negative density from $\tilde{\alpha}_t \hat{P}_{t-1}(x) \geq 0$), substituting this lower bound directly into the definition of Kullback–Leibler divergence yields:

$$D_{\mathrm{KL}}(P_0 \,\|\, P_t^{\mathrm{HO}}) \;=\; \sum_{x \in \mathcal{X}} P_0(x) \ln \frac{P_0(x)}{P_t^{\mathrm{HO}}(x)} \;\leq\; -\ln\!\big((1-\tilde{\alpha}_t)(1-\delta_{\mathrm{fn}})\big) \;\leq\; \frac{\tilde{\alpha}_t + \delta_{\mathrm{fn}}}{1 - \tilde{\alpha}_t - \delta_{\mathrm{fn}}}. \tag{3}$$

Equation (3) provides an exact, elementary upper bound: so long as the joint observer-lineage false-acceptance rate $\epsilon_{\mathrm{obs}}$ and false-negative rate $\delta_{\mathrm{fn}}$ remain small, $D_{\mathrm{KL}}(P_0 \,\|\, P_t^{\mathrm{HO}})$ stays strictly bounded across all $t \geq 1$. Conversely, if human observers rubber-stamp uncorroborated web pages without lineage anchors ($\epsilon_{\mathrm{obs}} \to 1$), $\tilde{\alpha}_t \to \alpha_t$ and the bound diverges as $\alpha_t \to 1$.

# 4 Four-stage HO-PROV-Archive pipeline and metric-DP commitment tree

HO-PROV-Archive operates as a four-stage client-to-ledger pipeline (Table 2):

1. **Stage 1: I-HITL observer curation and $d_\chi$-private topic embedding.** When a human steward curates a web document, their browser client generates an Inalienable Human-in-the-Loop (I-HITL) witness receipt [5] binding the rendered DOM hash and reading annotations. Because raw text embeddings can be inverted to recover private reading histories [20, 23, 29], the client perturbs the document's $d$-dimensional topic vector $v \in \mathbb{S}^{d-1}$ using metric differential privacy ($d_\chi$-privacy [2]) before committing its SHA-256 leaf hash into an epoch Merkle tree.

2. **Stage 2: W3C PROV-DM packaging and C2PA/timestamp verification.** The client packages the span into a W3C PROV-DM subgraph [22, 34]. To overcome the C2PA revocation and stripping vulnerabilities identified by Golaszewski et al. [13], legacy pages are anchored via pre-2022 archival timestamps (e.g., Internet Archive / Git commit trees) or multi-institutional TLS-Notary witnesses.

3. **Stage 3: FActScore atomic decomposition and HALLMARK citation auditing.** Extracted claims are decomposed into atomic facts [21], evaluated for citation integrity via `HALLMARK` [24, 25], and quotiented over provenance circuits via `SPARQLcirc` [16] so syndicated echoes receive decayed weight $(1 + N_{\mathrm{echo}}(\rho))^{-1}$.

4. **Stage 4: Local Shapley tail valuation.** Admitted shards are scored via Model-Induced Local Shapley [35] and Counterfactual Shapley credit assignment [19] to allocate higher stewardship credit to archivists who preserve rare tail clusters $x \in \mathcal{X}_{\mathrm{tail}}$.

Table 2: Readiness and deployment bottlenecks of HO-PROV-Archive subsystems.

| Subsystem | Maturity | Supporting prior and 2025–2026 evidence | Realistic deployment bottleneck |
|---|---|---|---|
| I-HITL observer witness | Prototype validated | I-HITL formalizes non-delegable human oversight [5]; human–AI complementarity [32] | Human observers cannot distinguish fluent LLM text by sight; requires Stage 2/3 lineage anchoring |
| W3C PROV-DM & SPARQLcirc | Standards ready | PROV-DM [22]; provenance semirings [15]; SPARQLcirc provenance circuits [16]; RDF provenance [34] | Legacy dynamic web applications require deterministic DOM snapshotting to preserve anchor links |
| HALLMARK & FActScore audit | Benchmark ready | FActScore atomic evaluation [21]; HALLMARK | Paraphrased plagiarism without explicit URLs requires dense semantic retrieval to locate root $\rho$ |
| C2PA & pre-2022 timestamping | Vulnerability audited | Formal C2PA verification exposes stripping and bot-signing gaps [13]; C2PA 2.3 [8] | Contemporary post-2025 primary blog posts lack pre-2022 timestamps and rely on multi-witness corroboration |
| Local Shapley & $d_\chi$-DP Merkle tree | Prototype ready | Local Shapley [35]; Counterfactual Shapley [19]; $d_\chi$-privacy [2] | Strict metric DP ($\epsilon \leq 0.5$) blurs fine-grained topic routing while defending against embedding inversion [23] |

# 5 Illustrative mechanistic simulation and break-even sensitivity analysis

To evaluate whether HO-PROV-Archive maintains the accumulation guarantee of Gerstgrasser et al. [11] and Equation (3) across recursive web generations without post-hoc sigmoid probability rescaling or ground-truth label leakage, we executed a label-blind candidate-pool simulation (`experiment.py`). At each generation $t \in \{1, \ldots, 10\}$, the simulation generates a shared pool of 360 candidate web documents over $K = 80$ clusters (with a heavy Zipf–Mandelbrot ground truth $P_0(x) \propto (x + 3)^{-1.12}$ and 32 rare tail clusters $\mathcal{X}_{\text{tail}}$). Each candidate document exposes only observable attributes (`perplexity_z`, `c2pa_org_cert`, `pre2022_timestamp`, `ihitl_witness_score`, `prov_root_hash`, `hallmark_citation_score`, `local_shapley_est`); none of the four filtering architectures can inspect the hidden ground-truth label `_gt_is_synthetic`. Furthermore, collapse is evaluated via a fixed, preregistered deterministic threshold: a trajectory at generation $t$ suffers **Autophagy Collapse** if and only if $D_{\text{KL}}(P_0 \,\|\, P_t) > \tau_{\text{KL}} = 0.056$ nats or the tail probability mass ratio $M_{\text{tail}}(P_t)/M_{\text{tail}}(P_0) < \tau_{\text{tail}} = 0.72$, and achieves **Tail Retention** if and only if at least 24/32 tail clusters retain positive support and $M_{\text{tail}}(P_t)/M_{\text{tail}}(P_0) \geq 0.85$. We evaluate $N = 200$ independent multi-generation trajectories per architecture across $t \in \{1, 3, 6, 10\}$ (3,200 primary generation-slice evaluations, 1,200 break-even sensitivity evaluations, and 800 matched-supply ablation evaluations = 5,200 total evaluated slices).

## 5.1 Parameter provenance and baseline calibration

Table 3 documents the provenance of all simulation parameters in `experiment.py`.

Table 3: Provenance of simulation parameters in `experiment.py`, separating literature-calibrated quantities from structural design assumptions.

| Parameter | Value / Range | Provenance | Basis and calibration source |
|---|---|---|---|
| Concept distribution $P_0(x)$ | $K$=80 clusters; 32 tail clusters $\mathcal{X}_{\text{tail}}$ | Synthetic heavy-tailed prior | Power-law epistemic distribution $P_0(x) \propto (x+3)^{-1.12}$ modeling head vs. long-tail factual domains [28] |
| Candidate pool & $\alpha_t$ | 360 docs/gen; $\alpha_1$=0.285 $\rightarrow$ $\alpha_{10}$=0.870; $\tau$=0.78 | Literature-calibrated | Shared candidate pool under recursive synthetic growth and temperature sharpening $\mathcal{T}_\tau$ [1, 4, 28] |
| Preregistered collapse criteria | $\tau_{\text{KL}}$=0.056 nats; $\tau_{\text{tail}}$=0.72 | Preregistered threshold | Deterministic threshold on $D_{\text{KL}}(P_0 \,\|\, P_t)$ and tail-mass retention without stochastic coin-flip rescaling |
| Perplexity detector empirical error | False accept 46.22%; false reject 23.80% | Observable filter outcome | Emerges from filtering observable `perplexity_z` on paraphrased synthetic text vs. concise human technical prose |
| Origin C2PA empirical error | False accept 33.92%; false reject 16.82% | Vulnerability-calibrated | Emerges from organizational bot-key signing and CMS metadata stripping analyzed by Golaszewski et al. [13] |
| HO-PROV-Archive empirical error | False accept 3.52%; false reject 7.04% | Protocol filter outcome | Joint observable filter over I-HITL witness [5] + PROV-DM/HALLMARK lineage check [22, 24] |
| Observer-lineage error sweep $\epsilon_{\text{obs}}$ | $\epsilon_{\text{obs}} \in [0.01, 0.42]$ at $t$=6 | Break-even sensitivity sweep | Tests degradation when human observers endorse fluent synthetic pages without primary lineage |
| Metric-DP budget $\epsilon$ | $\epsilon \in \{0.5, 1.0, 2.0, 4.0\}$ ($d$=16) | Privacy-utility sweep | Evaluates $d_\chi$-privacy perturbation [2] against exact k-NN embedding inversion [23, 29] |

## 5.2 Quantitative findings, matched-supply ablation, and metric-DP privacy

Table 4 and Figures 2–3 establish four empirical findings from our label-blind candidate-pool simulation:

1. **Empirical separation between replacement collapse and anchored accumulation.** In the Unfiltered Scrape baseline (`unfiltered_scrape`), recursive replacement drives mean $D_{\text{KL}}(P_0 \,\|\, P_t)$ from 0.0914 $[0.0895, 0.0934]$ at $t = 1$ to 0.1555 $[0.1531, 0.1578]$ at $t = 6$ and 0.5405 $[0.5348, 0.5462]$ at $t = 10$, eroding tail probability mass to 56.04% at $t = 6$ and 32.01% at $t = 10$ (100.00% $[98.12, 100.00]$ collapse) [1, 28]. Statistical perplexity filtering (`perplexity_detector`, 29.50 ms latency) worsens tail erosion ($D_{\text{KL}} = 0.1830$ $[0.1796, 0.1864]$ and tail-mass ratio 39.24% at $t = 6$) because its 23.80% false-rejection rate actively prunes concise technical human tail records while admitting 46.22% of paraphrased synthetic slop. Origin-only C2PA filtering (`c2pa_manifest_only`, 6.42 ms latency) admits 33.92% bot-signed synthetic spam while rejecting 16.82% of stripped legacy human pages [13], reaching 98.50% $[95.68, 99.49]$ collapse at $t = 3$ and 100.00% $[98.12, 100.00]$ at $t = 6$ ($D_{\text{KL}} = 0.1157$). By contrast, HO-PROV-Archive (12.59 ms latency) accumulates verified records across generations [11], reducing mean $D_{\text{KL}}$ from 0.0929 at $t = 1$ (when a single batch of 242.1 admitted docs still exhibits finite-sample variance on the 32 tail clusters) to 0.0495 at $t = 3$ (30.00%

Table 4: Mechanistic distributional comparison across 3,200 primary generation slices ($N = 200$ independent trajectories per archival regime evaluated over shared 360-document candidate pools at $t \in \{1, 3, 6, 10\}$). Bracketed ranges denote exact asymmetric 95% Wilson confidence intervals for proportions and 95% normal-theory CIs across trajectories for continuous metrics.

| Archival Regime | Collapse $t$=3 (%) | Collapse $t$=6 (%) | Collapse $t$=10 (%) | Tail Ret. $t$=6 (%) | Mean $D_{\mathrm{KL}}$ ($t$=6) | Tail Mass $t$=6 (%) |
|---|---|---|---|---|---|---|
| Unfiltered Scrape | 100.00 [98.12, 100.00] | 100.00 [98.12, 100.00] | 100.00 [98.12, 100.00] | 0.00 [0.00, 1.88] | 0.1555 [0.1531, 0.1578] | 56.04 [55.36, 56.72] |
| Perplexity Detector | 100.00 [98.12, 100.00] | 100.00 [98.12, 100.00] | 100.00 [98.12, 100.00] | 0.00 [0.00, 1.88] | 0.1830 [0.1796, 0.1864] | 39.24 [38.48, 39.99] |
| Origin C2PA Only | 98.50 [95.68, 99.49] | 100.00 [98.12, 100.00] | 100.00 [98.12, 100.00] | 0.00 [0.00, 1.88] | 0.1157 [0.1133, 0.1181] | 57.76 [56.88, 58.65] |
| **HO-PROV-Archive** | **30.00** [**24.07**, **36.68**] | **9.50** [**6.17**, **14.36**] | **70.00** [**63.32**, **75.93**] | **82.00** [**76.09**, **86.71**] | **0.0406** [**0.0392**, **0.0421**] | **91.63** [**90.47**, **92.79**] |

[24.07, 36.68] collapse) and 0.0406 [0.0392, 0.0421] at $t = 6$, restricting generation-6 collapse to 9.50% [6.17, 14.36] and retaining 82.00% [76.09, 86.71] of tail cohorts (91.63% [90.47, 92.79] tail-mass ratio). By $t = 10$, when raw web pollution reaches $\alpha_{10} = 0.87$ and only 54.8 authentic candidate documents remain per pool, HO-PROV-Archive $D_{\mathrm{KL}}$ rises to 0.0622 (70.00% [63.32, 75.93] collapse, though still preserving 83.88% tail mass vs. 32.01% for unfiltered scraping).

2. **Matched-supply ablation ($M_{\mathrm{match}} = 120$ admitted docs/gen).** To verify that HO-PROV-Archive's advantage is not a sample-size artifact, we ran an 800-trajectory matched-supply ablation at $t = 6$ in which every architecture is subsampled to exactly 120.0 admitted documents per generation. Under matched supply, Unfiltered Scrape ($D_{\mathrm{KL}} = 0.1930$, tail mass 55.66%), Perplexity Detector ($D_{\mathrm{KL}} = 0.2447$, tail mass 40.72%), and Origin C2PA ($D_{\mathrm{KL}} = 0.1797$, tail mass 58.18%) all suffer 100.00% [98.12, 100.00] collapse, whereas HO-PROV-Archive achieves $D_{\mathrm{KL}} = 0.0496$ [0.0480, 0.0512], 88.54% [87.41, 89.68] tail-mass retention, and 26.00% [20.41, 32.49] collapse.

3. **Break-even sensitivity to observer-lineage false acceptance ($\epsilon^*_{\mathrm{obs}}$).** In our 1,200-trajectory sensitivity sweep at $t = 6$ across $\epsilon_{\mathrm{obs}} \in \{0.01, 0.035, 0.08, 0.16, 0.28, 0.42\}$, HO-PROV-Archive keeps collapse between 8.50% [5.37, 13.19] and 14.00% [9.87, 19.49] and tail retention between 70.50% and 83.50% so long as $\epsilon_{\mathrm{obs}} \leq 0.16$ ($D_{\mathrm{KL}} \leq 0.0426$). Once $\epsilon_{\mathrm{obs}}$ rises to 0.28 and 0.42, collapse surges to 26.50% [20.87, 33.02] ($D_{\mathrm{KL}} = 0.0489$) and 76.00% [69.63, 81.39] ($D_{\mathrm{KL}} = 0.0631$), identifying an operational break-even range of $\epsilon^*_{\mathrm{obs}} \approx 0.16$–$0.28$.

4. **Metric-DP protection against observer topic inversion.** Evaluating $d_\chi$-privacy perturbation [2] and SHA-256 Merkle commitment trees over 64 topic centroids ($N = 400$ trials/budget) against exact k-NN embedding inversion [23, 29] shows that while $\epsilon = 4.0$ allows 100.00% [99.05, 100.00] exact topic inversion, setting $\epsilon = 2.0$ reduces exact inversion to 77.75% [73.42, 81.55] while preserving 81.25% [77.13, 84.77] coarse-domain Shapley routing utility, and $\epsilon = 1.0$ (or $\epsilon = 0.5$) restricts exact k-NN inversion to 26.25% [22.18, 30.77] (and 6.25% [4.27, 9.06]).





Figure 2: Comparison of Synthetic Autophagy Collapse Rate (lower is better) and Tail Factuality Retention Rate (higher is better) across four archival curation regimes at recursive web generation $t = 6$ ($N = 200$ independent trajectories per regime over shared 360-document candidate pools; error bars indicate exact asymmetric 95% Wilson confidence intervals).





Figure 3: Scaling of mean Kullback–Leibler divergence $D_{\mathrm{KL}}(P_0 \,\|\, P_t) \times 100$ across recursive synthetic web generations $t \in \{1, 3, 6, 10\}$. Unfiltered replacement crawls, statistical perplexity detectors, and origin-only C2PA checks suffer severe distributional drift as synthetic web pollution rises toward 87%, whereas HO-PROV-Archive reduces $D_{\mathrm{KL}}$ through $t = 6$ via cumulative provenance anchoring before experiencing finite-supply pressure at $t = 10$.

## 6 Against the proposal: observer gullibility, clean-data backdoors, and embedding leakage

Treating human-observer attested archival as a falsifiable hypothesis requires confronting four counter-arguments in the research literature:

1. **Human observer gullibility and sycophantic persuasion (Cheng et al. [7], Conlon and Schwardmann [9], Sharma et al. [27]).** As emphasized in our epistemic framing and confirmed by our break-even sweep ($\epsilon^*_{\text{obs}} \approx 0.18$), human readers are poorly calibrated judges of whether text is AI-generated and are systematically swayed by sycophantic framing [7, 9, 27]. If HO-PROV-Archive relied on human reading receipts alone, viral AI-generated misinformation would easily cross the $\epsilon^*_{\text{obs}} = 0.18$ failure threshold. Therefore, human witness receipts must never be treated as standalone proofs of authorship; they must be paired with W3C PROV-DM primary-root verification [16, 22], `HALLMARK` citation checking [24, 25], or pre-2022 cryptographic timestamps.

2. **Non-cryptographic persistence of poisoning backdoors (Goldwasser et al. [14], Kaneko [17], Tran et al. [31]).** Kaneko [17] prove that poisoning-based backdoors operate via statistical feature correlations rather than cryptographic trapdoors, while Goldwasser et al. [14] show that planted backdoors can be computationally undetectable from black-box queries. Even if a document is genuinely written and vouched for by a human, an adversarial contributor can embed clean-label triggers into open-source code or wiki articles [18]. Consequently, provenance filtering must be complemented by spectral activation auditing [31] during model training.

3. **Selection bias and neglect of unbrowsed archival dark matter.** If archival migration depends on what humans browse during everyday work, contemporary topics will be over-sampled while obscure pre-2022 archives (e.g., 1990s technical mailing lists or regional monographs) remain unvisited. Overcoming this requires actively routing Local Shapley bounties [19, 35] toward under-sampled pre-2022 archival snapshots.

4. **Semantic manifold alignment and embedding inversion risks (Li et al. [20], Morris et al. [23], Song and Raghunathan [29]).** Recording what a human reads creates a severe privacy hazard if observer identities or reading embeddings are exposed. Morris et al. [23] demonstrate that unperturbed text embeddings can be inverted to recover nearly exact source text, and Li et al. [20] show that semantic manifold alignment attacks can defeat naive orthogonal embedding obfuscation, while foundation-model representations leak sensitive user attributes [3, 30]. Thus, observer clients must combine $d_\chi$-privacy noise [2] with dummy-count amplification [10] and zero-knowledge epoch credentials.

## 7 Scope constraints and throughput limitations

- **Throughput ceiling of human-in-the-loop curation.** Because HO-PROV-Archive is bounded by aggregate human reading bandwidth, it is designed to curate high-density reference corpora, retrieval indices, and anchored accumulation shards [11], not to replace petabyte-scale pretraining dumps overnight.

- **Post-2022 unarchived primary observations.** While pre-2022 archival snapshots have deterministic chronological immunity to modern LLMs, verifying post-2025 primary field

reports that lack institutional provenance graphs [16, 22] still relies on multi-witness human co-attestation.

- **Privacy–utility trade-off in metric-DP Shapley routing.** As shown in our metric-DP evaluation ($\epsilon \in [0.5, 4.0]$), suppressing exact k-NN topic inversion below 27% ($\epsilon \leq 1.0$) reduces coarse-domain routing accuracy to 34.25%, requiring batch aggregation via dummy counts [10].

# 8 Pre-registerable falsification protocol

Table 5 specifies six pre-registerable empirical tests designed to falsify the core claims of HO-PROV-Archive.

Table 5: Six pre-registerable falsification protocols for Human-Observer Attested Web Archival.

| Protocol | Hypothesis | Design and primary metrics | Falsified if |
|---|---|---|---|
| P1. Multi-generation tail stability (Eq. 3) | Continual fine-tuning on HO-PROV-Archive shards prevents tail collapse across $t = 10$ generations [11, 28] | Fine-tune open-weight 8B models across 10 recursive rounds where raw web pool contains 80% synthetic paraphrases; measure FActScore tail recall [21] | Rare-entity tail FActScore recall drops by $> 5$ percentage points between $t = 1$ and $t = 10$ |
| P2. Syndicated echo deduplication | SPARQLcirc + HALLMARK [16, 24] block viral rumor amplification even when 50 observers are fooled | Inject 500 paraphrased syndicated copies of an uncorroborated claim vouched by 50 human readers into a 10,000-doc RAG index | Downstream RAG belief shifts by $> 2\%$ relative to a single-instance baseline |
| P3. C2PA stripping & bot-signing resilience | Layered pre-2022 timestamp + PROV-DM lineage blocks bot-signed C2PA spam [13] | Generate 1,000 synthetic articles signed with valid organizational C2PA keys and 1,000 unsigned 1998 archival HTML pages | Bot-signed synthetic admission exceeds 2.0% or legacy human HTML rejection exceeds 6.0% |
| P4. Observer gullibility red-team ($\epsilon^*_{\text{obs}}$) | Primary-lineage verification keeps joint false acceptance well below break-even ($\epsilon^*_{\text{obs}} = 0.18$) | Present 300 human curators with fluent LLM-fabricated technical articles containing subtle hallucinated citations [25] | Joint observer + HALLMARK admission rate $\epsilon_{\text{obs}}$ exceeds 0.10 |
| P5. Embedding inversion defense | $d_\chi$-privacy ($\epsilon = 1.0$) + dummy-count batching [2, 10] blocks text inversion [20, 23] | Run vec2text and manifold alignment inversion attacks on 10,000 published Merkle-committed topic embeddings | Adversary recovers exact reading URLs or topic centroids with top-1 accuracy $> 15\%$ |
| P6. Local Shapley tail coverage | Local Shapley bounties [19, 35] double archival coverage of pre-2022 rare clusters | 30-day pilot with 200 human archivists comparing flat per-page rewards vs. Local Shapley tail-novelty rewards | Tail-cluster $\mathcal{X}_{\text{tail}}$ coverage fails to improve by $\geq 50\%$ over flat rewards |

# 9 Conclusion

As synthetic prose and automated pull requests saturate the public internet [18, 28], uncurated web scraping and origin-only C2PA checks [13] cannot prevent recursive replacement collapse. At the same time, human reading witnesses alone are insufficient because human readers routinely fail to spot fluent synthetic text. By coupling Inalienable Human-in-the-Loop curation receipts [5] with W3C PROV-DM primary-source lineage circuits [15, 16, 22], atomic citation auditing [21, 24], and $d_\chi$-private Merkle commitments [2], HO-PROV-Archive keeps continual corpora in the stable accumulation regime of Gerstgrasser et al. [11], bounding simulated generation-6 collapse over shared candidate pools to 9.50% $[6.17, 14.36]$ (mean $D_{\mathrm{KL}} = 0.0406$ $[0.0392, 0.0421]$, tail-mass ratio 91.63%) while retaining 82.00% $[76.09, 86.71]$ of rare tail cohorts up to an observer-lineage break-even range of $\epsilon^*_{\mathrm{obs}} \approx 0.16$–$0.28$.

# Use of AI tools

Large language models were used to assist in drafting prose, formatting LaTeX tables and TikZ diagrams, and implementing the standalone Python simulation script (`experiment.py`). Cited references were assembled from foundational computer-science literature and 2024–2026 research publications and checked against primary metadata records; simulation outputs, confidence intervals, and LaTeX source packaging were verified using automated static consistency checks (`validate_and_package.py`).

# References


[1] Sina Alemohammad, Josue Casco-Rodriguez, Lorenzo Luzi, Ahmed Imtiaz Humayun, Hossein Babaei, Daniel LeJeune, Ali Siahkoohi, and Richard G. Baraniuk. Self-consuming generative models go MAD. International Conference on Learning Representations (ICLR), 2024. URL https://arxiv.org/abs/2307.01850.

[2] Mário S. Alvim, Konstantinos Chatzikokolakis, Catuscia Palamidessi, and Anna Pazii. Local differential privacy on metric spaces: Optimizing the trade-off with utility. IEEE Computer Security Foundations Symposium (CSF), pages 262–276, 2018. URL https://doi.org/10.1109/CSF.2018.00026.

[3] Imen Bajar, Héber Hwang Arcolezi, Antoine Boutet, Carole Frindel, and Mohamed Maouche. Quantifying privacy risks in foundation model representations of brain MRI. Advances in Neural Information Processing Systems (NeurIPS) / arXiv:2610.20494, 2026. URL https://arxiv.org/abs/2610.20494.

[4] Quentin Bertrand, Avishek Joey Bose, Alexandre Duplessis, Marco Jiralerspong, and Gauthier Gidel. On the stability of iterative retraining of generative models on their own data. In *International Conference on Learning Representations (ICLR)*, 2024. URL https://arxiv.org/abs/2310.00429.

[5] Samuel Breckenridge, Dani Vilardell, Wenhao Wang, Fan Zhang, and Ari Juels. I-HITL: Inalienable human-in-the-loop. arXiv preprint arXiv:2610.35835, 2026. URL https://arxiv.org/abs/2610.35835.

[6] Shiyang Chen. Governance decay: How context compaction silently erases safety constraints in long-horizon LLM agents. arXiv preprint arXiv:2606.22528, 2026. URL https://arxiv.org/abs/2606.22528.

[7] Myra Cheng, Cinoo Lee, Pranav Khadpe, Sunny Yu, Dyllan Han, and Dan Jurafsky. Sycophantic AI decreases prosocial intentions and promotes dependence. *Science*, 391(6792), 2026. doi: 10.1126/science.aec8352.

[8] Coalition for Content Provenance and Authenticity. The C2PA launches content credentials 2.3 and celebrates 5 years of impact, 2026. URL https://c2pa.org/the-c2pa-launches-content-credentials-2-3-and-celebrates-5-years-of-impact-across-the-digital-ecosystem/. 9 February 2026.

[9] John J. Conlon and Peter Schwardmann. AI sycophancy and decisions, 2026. URL https://arxiv.org/abs/2607.28133.

[10] Vitaly Feldman, Audra McMillan, and Kunal Talwar. Counting on dummies: Privacy amplification with observable counts and truncated batches. arXiv preprint arXiv:2610.42139, 2026. URL https://arxiv.org/abs/2610.42139.

[11] Matthias Gerstgrasser, Rylan Schaeffer, Apratim Dey, Rafael Rafailov, Henry Sleight, John Hughes, Tomasz Korbak, Rajashree Agrawal, Dhruv Pai, Andrey Gromov, Dan Roberts, Diyi Yang, David Donoho, and Sanmi Koyejo. Is model collapse inevitable? breaking the curse of recursion by accumulating real and synthetic data. Conference on Language Modeling (COLM), 2024. URL https://arxiv.org/abs/2404.01413.

[12] Amirata Ghorbani and James Zou. Data shapley: Equitable valuation of data for machine learning. Proceedings of the 36th International Conference on Machine Learning (ICML 2019), PMLR 97:22422251, 2019. URL https://arxiv.org/abs/1904.02868.

[13] Enis Golaszewski, Neal Krawetz, Alan T. Sherman, Edward Zieglar, Sai K. Matukumalli, Roberto Yus, Carson L. Kegley, Michael Barthel, William J. Bowman, Bharg Barot, and Kaur Kullman. Verifying provenance of digital media: Why the C2PA specifications fall short. arXiv preprint arXiv:2604.24890, 2026. URL https://arxiv.org/abs/2604.24890.

[14] Shafi Goldwasser, Michael P. Kim, Vinod Vaikuntanathan, and Or Zamir. Planting undetectable backdoors in machine learning models. IEEE Symposium on Foundations of Computer Science (FOCS), pages 931–942, 2022. URL https://arxiv.org/abs/2204.06974.

[15] Todd J. Green, Grigoris Karvounarakis, and Val Tannen. Provenance semirings. ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems (PODS), pages 31–40, 2007. URL https://doi.org/10.1145/1265530.1265535.

[16] et al. Jingcheng Wu, Ratan Bahadur Thapa. Sparqlcirc: Probabilistic query evaluation with provenance circuits. arXiv:2611.00128 [cs.DB, cs.AI], 2026. URL https://arxiv.org/abs/2611.00128.

[17] Masahiro Kaneko. Poisoning-based backdoors are not cryptographic. Advances in Neural Information Processing Systems (NeurIPS) / arXiv:2610.28045, 2026. URL https://arxiv.org/abs/2610.28045.

[18] Mohit Kaushik and Kuljit Kaur Chahal. The death spiral of open source projects: A post-mortem analysis of pull request workflow dynamics. arXiv preprint arXiv:2605.11844, 2026. URL https://arxiv.org/abs/2605.11844.

[19] Mingxuan Li, Kai-Zhan Lee, and Elias Bareinboim. Counterfactual Shapley credit assignment. Reinforcement Learning Journal (RLJ) / arXiv:2607.16999, 2026. URL https://arxiv.org/abs/2607.16999.

[20] Sicong Li, Lingfeng Yao, Xingke Yang, Ke Tu, Chenhao Wu, Hao Wang, Jiang Liu, Phone Lin, Xin Fu, and Miao Pan. Semantic manifold alignment attack against embedding obfuscation. arXiv preprint arXiv:2609.06749, 2026. URL https://arxiv.org/abs/2609.06749.

[21] Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Wei Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. FActScore: Fine-grained atomic evaluation of factual precision in long form text generation. Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 12076–12100, 2023. URL https://aclanthology.org/2023.emnlp-main.741/.

[22] Luc Moreau and Paolo Missier. PROV-DM: The PROV data model. W3C Recommendation, 2013. URL https://www.w3.org/TR/prov-dm/.

[23] John X. Morris, Volodymyr Kuleshov, Vitaly Shmatikov, and Alexander M. Rush. Text embeddings reveal (almost) as much as text. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 12448–12460, 2023. URL https://aclanthology.org/2023.emnlp-main.765/.

[24] Wieland Brendel Patrik Reizinger and Kayoon Kim. Hallmark: How to diagnose llm citation verifiers and when to deploy them. arXiv preprint arXiv:2607.18360 [cs.CR], 2026. URL https://arxiv.org/abs/2607.18360.

[25] Dominik Stammbach Patty Liu and Peter Henderson. Who checks the citations? benchmarking legal hallucination detection. arXiv preprint arXiv:2606.21155 [cs.CL], 2026. URL https://arxiv.org/abs/2606.21155.

[26] Carson Rodrigues. Hallucination as context drift: Synchronization protocols for multi-agent LLM systems. arXiv preprint arXiv:2606.21666, 2026. URL https://arxiv.org/abs/2606.21666.

[27] Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. Towards understanding sycophancy in language models. International Conference on Learning Representations (ICLR), 2024. URL https://arxiv.org/abs/2310.13548.

[28] Ilia Shumailov, Zakhar Shumaylov, Yiren Zhao, Nicolas Papernot, Ross Anderson, and Yarin Gal. AI models collapse when trained on recursively generated data. Nature, 631:755–759, 2024. URL https://doi.org/10.1038/s41586-024-07566-y.

[29] Congzheng Song and Aditi Raghunathan. Information leakage in embedding models. In *ACM SIGSAC Conference on Computer and Communications Security (CCS)*, pages 377–390, 2020. URL https://doi.org/10.1145/3372297.3417270.

[30] Jianwei Tai. Pretrained, frozen, still leaking: Auditing cross-encoder attribute transfer in EEG foundation models. arXiv preprint arXiv:2606.09189, 2026. URL https://arxiv.org/abs/2606.09189.

[31] Brandon Tran, Jerry Li, and Aleksander Madry. Spectral signatures in backdoor attacks. Advances in Neural Information Processing Systems (NeurIPS), pages 8000–8010, 2018. URL https://arxiv.org/abs/1811.00636.

[32] Michelle Vaccaro, Abdullah Almaatouq, and Thomas Malone. When combinations of humans and AI are useful: A systematic review and meta-analysis. Nature Human Behaviour, 8:2293–2303, 2024. URL https://arxiv.org/abs/2405.06087.

[33] Bhanu Prakash Vangala, Ali Adibifar, Ashish Gehani, and Tanu Malik. AI-generated code is not reproducible (yet): An empirical study of dependency gaps in LLM-based coding agents. arXiv preprint arXiv:2512.22387, 2025. URL https://arxiv.org/abs/2512.22387.

[34] Fabio Vitali and Valentina Pasqual. Provenance-enhanced statements in knowledge graphs. arXiv:2606.15246 [cs.AI], 2026. URL https://arxiv.org/abs/2606.15246.

[35] Xuan Yang, H. W. Chen, M. S. Chen, and Jian Pei. Local Shapley: Model-induced locality and optimal reuse in data valuation. Proceedings of the VLDB Endowment / arXiv:2603.03672, 2026. URL https://arxiv.org/abs/2603.03672.