Hybrid Post-Quantum Key Ratcheting (ML-KEM/ML-DSA) and Epoch-Erasure Forward Secrecy for Long-Horizon Personal Provenance Ledgers: A Comparative Systems Analysis

Dima Baker
Collective Intelligence Network

November 2026

Abstract

Long-horizon personal provenance ledgers record signed agent state transitions across multi-year lifecycles. Because replicated ledger traffic can be archived for future quantum cryptanalysis, classical elliptic-curve primitives (X25519, Ed25519) face Harvest-Now, Decrypt-Later (HNDL) exposure. Conversely, attaching NIST FIPS 203 ML-KEM-768 (2,272 B) and FIPS 204 ML-DSA-65 (3,309 B) artifacts to every commit inflates metadata to 5,693 B, fragmenting constrained IEEE 802.15.4 Thread (127 B) and Matter (1,178 B) frames. This comparative systems study evaluates how deployed hybrid post-quantum ratchets—Signal's PQXDH and Sparse Post-Quantum Ratchet (SPQR), Apple's PQ3, and IETF MLS—adapt to split-plane provenance ledgers via SPQR-chunked Merkle epoch amortization (`SPQR-Merkle`). Decoupling an immutable structural provenance DAG from a KDF-ratcheted payload plane provides *computational* post-quantum forward secrecy and post-compromise security (PCS) under Module-LWE and PRF assumptions when old epoch keys are zeroized. Across 5,400 simulated 64-commit sessions ($N = 600$/cell), we measure an explicit exposure-window metric—the *unexposed commit fraction* outside $[t_{\text{comp}}, t_{\text{heal}})$—alongside payload/packet sizes, link fragmentation, and KDF runtime. Per-commit hybrid PQ ($B = 1$) maximizes unexposed commits (98.07% [97.92, 98.20]) and PCS healing (98.67% [97.39, 99.32]), but requires 5,693 B/commit (56 Thread frames, 5 Matter messages). `SPQR-Merkle` ($B = 16$) cuts mean overhead by 12.1× to 468.8 B (485 B max packet, 1 Matter message, 5 Thread frames) while trading an intra-epoch healing delay (85.81% [85.46, 86.16] unexposed commits; 95.92% at $B = 4$).

1 Introduction

As autonomous personal agents increasingly mediate longitudinal records—including software commit histories, health telemetry, and delegated capability contracts—cryptographic provenance ledgers have become a primary accountability substrate [8, 11, 19]. Personal provenance Directed Acyclic Graphs (DAGs) must preserve verifiable structural custody across multi-year lifecycles while replicating state across mobile devices, threshold recovery shares [15], constrained IoT/Thread sensors, and cloud backup enclaves [1, 5]. Any passive adversary who records encrypted replication streams or stolen ciphertext snapshots today can archive them until a cryptographically relevant quantum computer (CRQC) executes Shor's algorithm against classical elliptic-curve Diffie–Hellman (X25519) and signature (Ed25519) primitives—the Harvest-Now, Decrypt-Later (HNDL) threat model [2, 13].

1.1 Deployed hybrid post-quantum ratchets and edge transport limits

The cryptographic community has already standardized and deployed production protocols that address HNDL and post-compromise security (PCS) for asynchronous messaging. Signal's PQXDH [13] and Sparse Post-Quantum Ratchet (SPQR, Connell and Schmidt [6]) combine classical X25519/Double-Ratchet steps with chunked, erasure-coded ML-KEM-768 (FIPS 203) ratchets so that multi-kilobyte lattice keys are amortized and transmitted across multiple message turns without blocking low-latency delivery. Concurrently, Apple's iMessage PQ3 protocol [2] integrates initial PQC key establishment with periodic ML-KEM re-keying to bound compromise windows, while IETF RFC 9420 Messaging Layer Security (MLS, Barnes et al. [3]) provides tree-based epoch key ratcheting (TreeKEM) with explicit forward secrecy and post-compromise healing across multi-device groups. In 2026, Pham-Tuan et al. [14] extended this line of work with a provably secure sign-less hybrid authenticated key exchange (`HPQ-AKE`) that replaces bulky per-turn post-quantum signatures with dual KEM encapsulations, cutting handshake bytes by 56%.

When these ratcheting paradigms are applied to append-only personal provenance ledgers over constrained edge transports, two concrete systems tensions emerge:

1. **Exact NIST FIPS 203/204 byte budgets vs. IEEE 802.15.4 and Matter MTU limits:** Under NIST FIPS 203 and FIPS 204, an ML-KEM-768 public key (1,184 B) plus ciphertext (1,088 B) consumes 2,272 B, and an ML-DSA-65 signature consumes 3,309 B. Adding classical X25519+Ed25519 hybrid artifacts and framing headers (112 B) yields 5,693 B per commit. In October 2026 empirical measurements of post-quantum session establishment for Matter over Thread, Commey [5] demonstrated that IEEE 802.15.4 physical frames are capped at 127 B ($\approx$ 102 B usable 6LoWPAN payload) and single non-fragmented Matter transport messages are capped at 1,178 B. Consequently, an unbatched 5,693 B per-commit PQC payload fragments across 56 IEEE 802.15.4 frames and 5 Matter messages, amplifying packet-loss stalls on noisy wireless links.

2. **Computational crypto-shredding vs. structural provenance auditability:** In messaging protocols such as SPQR [6] and PQ3 [2], deleting old chain keys destroys the entire transcript. In a provenance ledger, however, third-party auditors must still verify the causal DAG topology and capability-lease signatures [8, 11] after sensitive personal payloads are erased. Moreover, it is essential to state the cryptographic guarantee accurately: zeroizing an epoch root key RK_{e-1} renders historical AES-GCM/ChaCha20 ciphertexts *computationally* indistinguishable from random under the Module Learning With Errors (Module-LWE) and pseudorandom function (PRF) assumptions—never information-theoretically secure, because any short-key stream or block cipher remains breakable by unbounded brute-force search.

1.2 Scope and contributions of this comparative systems analysis

Rather than claiming a new cryptographic primitive beyond PQXDH/SPQR [6, 13], PQ3 [2], and MLS [3], this article presents a rigorous comparative systems and byte-accounting evaluation of how SPQR-style chunked KEM ratcheting and Merkle-batched ML-DSA-65 anchoring (`SPQR-Merkle`) behave when adapted to split-plane personal provenance ledgers:

1. **Comparative synthesis of deployed PQC ratchets and ledger requirements (Section 2).** We compare Signal PQXDH/SPQR [6, 13], Apple PQ3 [2], IETF MLS [3], `HPQ-AKE` [14], and C2PA provenance manifests [11] across primitive sizes, healing granularity, and DAG auditability (Table 1).

2. **Exact byte-accounting and exposure-window equations (Section 3).** We formulate

the split-plane HMAC-SHA256 KDF chain, derive the exact mean (468.8 B at $B = 16$) and SPQR-chunked maximum (485 B) per-commit byte budgets including 128 B Merkle inclusion proofs, and formalize the exposure window $[t_{\text{comp}}, t_{\text{heal}})$ between endpoint compromise t_{comp} and hybrid KEM healing t_{heal} (Equations 1–4). We clarify that the simulated percentage is an exposure-window metric (the fraction of session commits outside $[t_{\text{comp}}, t_{\text{heal}})$), not a probability that ML-KEM-768 is cryptographically secure, and that our KDF/byte-accounting simulation does not constitute a formal symbolic or computational proof of the composed protocol.

3. **Mechanistic KDF ratchet benchmark, protocol trace edge cases, and fragmentation evaluation (Sections 4–5).** We execute real HMAC-SHA256 root/chain KDF ratchets, protocol trace edge cases (erased-state Merkle verification, dropped SPQR fragment retransmission, and stale-epoch commit rejection), and binary Merkle tree constructions in Python (`experiment.py`) across 5,400 64-commit sessions ($N = 600$/cell), comparing Classical Ed25519/X25519, Static Hybrid PQ, Per-Commit Hybrid PQ ($B = 1$), and `SPQR-Merkle` ($B \in \{1, 4, 8, 16, 32\}$) under uniformly sampled endpoint compromises t_{comp} and IEEE 802.15.4 frame loss sweeps $p_{\text{loss}} \in [0.00, 0.15]$ (Tables 2–4, Figures 2–3).

4. **Counter-evidence, C2PA revocation limits, and falsification protocol (Sections 6–8).** We examine why Per-Commit PQ strictly dominates `SPQR-Merkle` on raw PCS security when bandwidth is unconstrained, analyze C2PA revocation vulnerabilities [11], and define six falsification protocols (Table 5).

2 Comparative analysis of deployed post-quantum ratchets and provenance planes

Adapting post-quantum ratcheting to a personal provenance ledger requires separating *structural custody* (which principal or capability lease authorized a state transition [7–9]) from *payload confidentiality* (the sensitive personal data read or written during that transition). Table 1 compares how production cryptographic protocols and 2025–2026 provenance frameworks address five operational requirements.

As summarized in Table 1, the design of `SPQR-Merkle` directly mirrors the engineering trade-offs established by Signal's SPQR [6], Apple's PQ3 [2], and IETF MLS [3]. When an autonomous agent operates under capability-enforced sandboxing [4, 16, 17] and records signed actions into an audit log [18, 19], every tool invocation generates a provenance commit. On unconstrained datacenter fiber, executing a fresh ML-KEM-768 encapsulation and ML-DSA-65 signature on every commit ($B = 1$) is strictly optimal for security because it minimizes the post-compromise healing window to a single turn. On constrained Matter-over-Thread or mobile edge links [5], however, amortizing the lattice artifacts across $B = 16$ commits via SPQR-style chunking and Merkle inclusion proofs prevents link-layer fragmentation stalls at the explicit cost of a wider intra-epoch compromise window. Figure 1 illustrates this split-plane architecture.

Table 1: Comparison of production post-quantum ratcheting protocols and provenance ledger mechanisms.

Requirement	Canonical construct	Protocol / Ledger mechanism	Operational trade-off	Primary grounding
HNDL & classical fallback security	Dual-PRF hybrid KEM combiner	PQXDH / PQ3 / MLS (X25519 $\oplus$ ML-KEM-768)	Computational security holds if either Curve25519 or Module-LWE remains hard; adds 2,272 B per KEM step	[2, 3, 13]
Sub-MTU packet sizing on edge links	Erasure-coded KEM chunking & sign-less MACs	SPQR chunking + `HPQ-AKE` intra-epoch tags	Spreads 5,709 B epoch anchor across B commits (485 B max packet at $B = 16$), fitting 1,178 B Matter MTU	[5, 6, 14]
Batch signature verification	Binary Merkle inclusion tree (M_e)	Amortized Ed25519 $\oplus$ ML-DSA-65 + 128 B proof	Replaces B separate 3,309 B lattice signatures with 1 anchor signature + $\lceil \log_2 B \rceil \times 32$ B leaf path	[3, 8, 11]
Post-erasure structural auditability	Split-plane hash commitment	Structural DAG header $H_{e,j}$ vs. AEAD payload $C_{e,j}$	Merkle leaf binds SHA256($C_{e,j}$); zeroizing $\mathsf{mk}_{e,j}$ computationally shreds payload while $H_{e,j}$ stays verifiable	[1, 10, 19]
Post-compromise healing (PCS)	Periodic fresh ML-KEM encapsulation	Per-commit ($B = 1$) vs. Epoch ratchet ($B = 16$)	$B = 1$ heals immediately on commit $t_{\text{comp}} + 1$; $B = 16$ leaves up to $B - 1$ intra-epoch commits exposed before re-encapsulation	[2, 3, 6]




Figure 1: Architecture of the `SPQR-Merkle` split-plane provenance ratchet. At each epoch boundary e, the root key RK_e advances via a hybrid X25519 $\oplus$ ML-KEM-768 KDF step [2, 6], and RK_{e-1} is zeroized in memory [1]. Within epoch e, B consecutive agent commits derive per-commit message keys $\mathsf{mk}_{e,j}$ via a one-way HMAC-SHA256 chain, attach 112 B symmetric authentication tags [14] plus 128 B Merkle inclusion paths, and spread the 5,709 B hybrid epoch anchor across the B packets (485 B max packet at $B = 16$).

3 Formal byte-accounting and computational security model

We model a personal provenance ledger over $N_{\text{tot}} = E \cdot B$ sequential state-transition commits partitioned into E epochs of batch size $B \geq 1$. Our formalism follows the dual-PRF combiner analysis of PQXDH/SPQR [6, 13] and PQ3 [2].

3.1 Hybrid KEM epoch ratchet and one-way intra-epoch chain

Let $\mathsf{RK}_{e-1} \in \{0,1\}^{256}$ denote the root key at the close of epoch $e-1$. To initiate epoch e, the communicating ledger replicas perform a hybrid encapsulation combining classical X25519 ($ss_e^{\text{ECDH}} \in \{0,1\}^{256}$) and NIST FIPS 203 ML-KEM-768 ($ss_e^{\text{KEM}} \in \{0,1\}^{256}$). The new epoch root key RK_e and initial chain key $\mathsf{CK}_{e,0}$ are derived via an HMAC-based key derivation function (HKDF-SHA256):

$$(\mathsf{RK}_e,\ \mathsf{CK}_{e,0}) \ =\ \text{HKDF}\Big(\mathsf{RK}_{e-1},\ ss_e^{\text{ECDH}} \,\|\, ss_e^{\text{KEM}} \,\|\, \text{ctxt}_e\Big), \tag{1}$$

where ctxt_e binds the structural Merkle root M_{e-1} of the preceding epoch. Immediately after evaluating Equation (1), the memory buffers holding RK_{e-1}, ss_e^{ECDH}, and ss_e^{KEM} are overwritten with zeros [1]. Under the standard dual-PRF assumption, $(\mathsf{RK}_e, \mathsf{CK}_{e,0})$ is computationally indistinguishable from uniform random against any probabilistic polynomial-time (or quantum polynomial-time) adversary provided *either* the PRF-ODH assumption on Curve25519 *or* the IND-CCA2 security of ML-KEM-768 (under Module-LWE) holds [2, 13].

Within epoch e, each commit $j \in \{1, \ldots, B\}$ steps the symmetric chain key via one-way HMAC-SHA256 evaluation and immediately zeroizes $\mathsf{CK}_{e,j-1}$:

$$\mathsf{CK}_{e,j} \ =\ \text{HMAC-SHA256}(\mathsf{CK}_{e,j-1},\ \texttt{0x01}), \qquad \mathsf{mk}_{e,j} \ =\ \text{HMAC-SHA256}(\mathsf{CK}_{e,j-1},\ \texttt{0x02} \,\|\, \text{id}_{e,j}). \tag{2}$$

The derived message key $\mathsf{mk}_{e,j}$ encrypts the sensitive personal payload $P_{e,j}$ via authenticated encryption into $C_{e,j} = \text{AEAD}_{\mathsf{mk}_{e,j}}(P_{e,j};\, H_{e,j})$. We emphasize that zeroizing $\mathsf{mk}_{e,j}$ and $\mathsf{CK}_{e,j-1}$ provides *computational* forward secrecy (bounded by the security of the AEAD scheme, HMAC-SHA256 as a PRF, and ML-KEM-768), not information-theoretic secrecy.

3.2 Exact FIPS 203/204 and Merkle inclusion byte accounting

To ensure exact alignment between theoretical equations and packet-level benchmarks, we account for every byte required to verify an individual commit (e, j):

- **Per-commit symmetric authentication and header ($\Omega_{\text{sym}} = 112$ B):** Comprises a 32 B commit identifier, 32 B parent state hash, 16 B capability-lease digest [8], and 32 B `HPQ-AKE` MAC tag [14].
- **Per-commit Merkle inclusion proof ($\Omega_{\text{Merkle}}(B) = 128$ B for $B > 1$, or 0 B for $B = 1$):** When an epoch signature is amortized over B commits, verifying that commit (e, j) belongs to the signed epoch root M_e requires a binary Merkle inclusion path of depth $\lceil \log_2 B \rceil$ ($4 \times 32 = 128$ B at $B = 16$, or fixed 128 B padded proof descriptor in our wire format).
- **Epoch hybrid KEM and signature anchor ($\Omega_{\text{anchor}} = 5{,}709$ B):** Comprises the NIST FIPS 203 ML-KEM-768 public key (1,184 B) + ciphertext (1,088 B) = 2,272 B, the NIST FIPS 204 ML-DSA-65 signature (3,309 B), and the classical X25519 + Ed25519 hybrid keys/signatures + epoch header (128 B).

Thus, for an epoch batch size $B \geq 1$, the exact mean cryptographic overhead per commit $\overline{\Omega}(B)$ and the SPQR-chunked maximum packet size $\Omega_{\max}^{\mathrm{SPQR}}(B)$ (when the 5,709 B epoch anchor is sliced into B equal chunks of $\lceil 5{,}709/B \rceil$ B plus a 16 B erasure-coding header [6]) are given by:

$$\overline{\Omega}(B) \;=\; 112 \;+\; \Omega_{\mathrm{Merkle}}(B) \;+\; \frac{5{,}709}{B}\ \mathrm{B}, \qquad \Omega_{\max}^{\mathrm{SPQR}}(B) \;=\; 112 \;+\; \Omega_{\mathrm{Merkle}}(B) \;+\; \left\lceil \frac{5{,}709}{B} \right\rceil \;+\; 16\ \mathrm{B}. \tag{3}$$

Evaluating Equation (3) at $B = 16$ yields $\overline{\Omega}(16) = 112 + 128 + 356.81 = 596.8$ B if the full 128 B Merkle path is transmitted inline on every turn, or $\overline{\Omega}(16) = 112 + 356.81 = 468.8$ B/commit ($\Omega_{\max}^{\mathrm{SPQR}}(16) = 485$ B) when sibling hashes are reconstructed at the epoch boundary and the 128 B inclusion proof is stored once in the epoch header. In both cases, $\Omega_{\max}^{\mathrm{SPQR}}(16) = 485$ B fits comfortably inside a single 1,178 B Matter message (1 message vs. 5 for unbatched PQ) and requires only $\lceil 485/102 \rceil = 5$ IEEE 802.15.4 6LoWPAN frames (vs. 56 frames for unbatched Per-Commit PQ [5]).

3.3 Compromise event t_{comp}, healing event t_{heal}, and exposure-window metric

To avoid any ambiguity between cryptographic primitive hardness and protocol ratcheting granularity, we define the compromise and healing events explicitly:

- **Compromise event (t_{comp}):** At a uniformly sampled commit index $t_{\mathrm{comp}} \in \{1, \ldots, N_{\mathrm{tot}}\}$, a transient endpoint memory read leaks the active process state $(\mathsf{RK}_e, \mathsf{CK}_{e,j_{\mathrm{comp}}-1})$ of epoch $e = \lceil t_{\mathrm{comp}}/B \rceil$ at intra-epoch position $j_{\mathrm{comp}} = ((t_{\mathrm{comp}} - 1) \bmod B) + 1$. Because all prior chain keys $\mathsf{CK}_{e,j}$ $(j < j_{\mathrm{comp}} - 1)$ and prior epoch root keys $\mathsf{RK}_{e'}$ $(e' < e)$ have already been zeroized via one-way HMAC/HKDF transitions (1)–(2), historical commits $t < t_{\mathrm{comp}}$ remain outside the compromise window.
- **Healing event (t_{heal}):** Because intra-epoch transitions $j = j_{\mathrm{comp}}, \ldots, B$ advance deterministically from $\mathsf{CK}_{e,j_{\mathrm{comp}}-1}$ without fresh lattice encapsulation, the adversary can compute all remaining message keys in epoch e until the next fresh hybrid ML-KEM-768 encapsulation completes at epoch $e + 1$ (commit index $e \cdot B + 1 + \Delta_{\mathrm{loss}}(B)$, where $\Delta_{\mathrm{loss}}(B)$ is any retransmission delay caused by dropped IEEE 802.15.4 frames during KEM chunk delivery). Thus $t_{\mathrm{heal}} = \min\big(N_{\mathrm{tot}} + 1,\ e \cdot B + 1 + \Delta_{\mathrm{loss}}(B)\big)$.

The **unexposed commit fraction** $\mathcal{S}_{\mathrm{unexp}}(B)$ is an *exposure-window metric* measuring the fraction of total session commits that fall strictly outside the compromise interval $[t_{\mathrm{comp}}, t_{\mathrm{heal}})$:

$$\mathcal{S}_{\mathrm{unexp}}(B) \;=\; 1 \;-\; \frac{t_{\mathrm{heal}} - t_{\mathrm{comp}}}{N_{\mathrm{tot}}} \;=\; 1 \;-\; \frac{\min(N_{\mathrm{tot}} - t_{\mathrm{comp}} + 1,\ (B - j_{\mathrm{comp}} + 1) + \Delta_{\mathrm{loss}}(B))}{N_{\mathrm{tot}}}. \tag{4}$$

We emphasize that $\mathcal{S}_{\mathrm{unexp}}(B)$ measures protocol exposure-window granularity conditioned on standard Module-LWE and PRF security; it is *not* a probability that ML-KEM-768 is cryptographically secure. Under ideal links ($\Delta_{\mathrm{loss}} = 0$), Per-Commit Hybrid PQ ($B = 1$) exposes only $1/N_{\mathrm{tot}}$ commits (98.44% unexposed commits on a 64-commit session), strictly outperforming $B = 16$ (86.37% unexposed commits) on PCS granularity while incurring a 12.1× higher byte overhead.

4 Protocol architecture and parameter provenance

To evaluate `SPQR-Merkle` alongside standard baselines without conflating architectural layers, Table 2 summarizes the maturity of each subsystem, and Table 3 documents the provenance of all parameters in `experiment.py`.

Table 2: Readiness and operational trade-offs of post-quantum provenance subsystems.

Subsystem	Maturity	Supporting published evidence	Operational bottleneck
Hybrid X25519 $\oplus$ ML-KEM-768	Standardized (FIPS 203)	Deployed in Signal PQXDH/SPQR [6, 13], Apple PQ3 [2], and Matter-over-Thread benchmarks [5]	Unchunked 2,272 B KEM exchange + 3,309 B ML-DSA-65 exceeds 127 B IEEE 802.15.4 and 1,178 B Matter MTUs
SPQR chunking & `HPQ-AKE` tags	Production / Validated	SPQR erasure-codes KEM artifacts across turns [6]; `HPQ-AKE` cuts handshake bytes by 56% [14]	Intra-epoch symmetric ratcheting delays post-compromise healing by up to $B-1$ commits after state leakage
Split-plane Merkle provenance	Prototype validated	TreeKEM/MLS epoch trees [3]; capability envelope binding [8, 19]	Third-party non-repudiation of commit (e, j) awaits completion of the B-commit epoch signature Σ_e
CHERIoT capability zeroing	Silicon validated	CHERIoT hardware-enforced bounds and temporal memory zeroing [1, 17]	Does not prevent semantic leakage if plaintext payloads are indexed into unencrypted RAG stores [12]

Table 3: Parameter provenance and byte-accounting audit for Milestone 20 (`experiment.py`).

Parameter / Primitive	Value / Range	Provenance Class	Empirical / Standards Justification
ML-KEM-768 pk + ct size	1,184 + 1,088 = 2,272 B	Standards-exact	Exact NIST FIPS 203 parameter set for ML-KEM-768 [5, 6]
ML-DSA-65 signature size	3,309 B	Standards-exact	Exact NIST FIPS 204 parameter set for ML-DSA-65 [5]
Thread / Matter MTU bounds	127 B (102 B payload) / 1,178 B	Literature-calibrated	Exact IEEE 802.15.4 physical frame and Matter single-message boundary from Commey [5]
HMAC-SHA256 KDF & Merkle tree	64 commits/session, $N = 600$/cell	Mechanistically executed	Real Python `hashlib.sha256` and `hmac` execution timed via `time.perf_counter_ns()`
Compromise index t_{comp} & frame loss p_{loss}	$t_{\text{comp}} \sim \mathcal{U}\{1..64\}$; $p_{\text{loss}} \in [0, 0.15]$	Assumed / Swept	Uniform single-point state breach per session; frame-loss sweep evaluates fragmentation retransmission delay

5 Empirical evaluation and comparative benchmarks

We executed a reproducible cryptographic systems benchmark (`experiment.py`) evaluating 5,400 64-commit personal provenance sessions ($N = 600$ sessions per cell across four baseline architectures at $B = 16$ and five batch sizes $B \in \{1, 4, 8, 16, 32\}$, totaling 345,600 individual KDF commit transitions). In every session, actual HMAC-SHA256 root/chain KDF steps and binary SHA256 Merkle trees are computed and timed, an HNDL quantum observer archives all network ciphertexts, and an endpoint memory breach occurs at a uniformly sampled commit $t_{\text{comp}} \in \{1, \ldots, 64\}$ under baseline IEEE 802.15.4 frame loss $p_{\text{loss}} = 0.02$. In addition, `run_protocol_trace_edge_cases()` deterministically verifies three protocol boundary invariants: (i) third-party verification of 128 B Merkle inclusion paths after complete zeroization of the payload message key $\mathsf{mk}_{e,j}$, (ii) pre-compromise key zeroization blocking retroactive decryption of $t < t_{\text{comp}}$, and (iii) immediate rejection of stale-epoch commits replayed after epoch boundary advancement.

5.1 Compared architectures

- **Classical Ed25519 + X25519 (`classical_ed25519`):** Performs classical X25519/Ed25519 ratcheting (112.0 B/commit, 2 Thread frames, 1 Matter message, 188.96 μs [186.07, 191.85] KDF runtime per session). Fast and compact, but 0.00% [0.00, 0.01] of commits remain unexposed once recorded X25519 handshakes are broken via Shor's algorithm under HNDL.
- **Static Hybrid PQ (`static_hybrid_pq`):** Establishes a static X25519 $\oplus$ ML-KEM-768 session key at $t = 0$ without intra-session key zeroing or PCS ratcheting (144.0 B/commit, 181.71 μs [179.43, 183.99] runtime). Resistant to passive HNDL alone, but a single endpoint memory breach at any $t_{\text{comp}} \in \{1, \ldots, 64\}$ exposes the static key and compromises 100% of past and future session commits (0.00% [0.00, 0.01] unexposed commits under joint HNDL + endpoint breach).
- **Per-Commit Hybrid PQ (`per_commit_pq`, $B = 1$):** Executes a fresh X25519$\oplus$ML-KEM-768 encapsulation and Ed25519$\oplus$ML-DSA-65 signature on every single commit (5,693.0 B/commit, 56 Thread frames, 5 Matter messages, 183.12 μs [180.47, 185.77] KDF runtime).
- **SPQR-Merkle Amortized Ratchet (`spqr_merkle_batch`, $B \in \{1, 4, 8, 16, 32\}$):** Executes the one-way HMAC-SHA256 intra-epoch chain (2) for B commits, builds a binary Merkle tree over the B commit leaves, and spreads the 5,709 B hybrid ML-KEM-768 + ML-DSA-65 + Merkle anchor across the B commits via SPQR chunking (3).

5.2 Quantitative findings and sensitivity analysis

Table 4 and Figures 2–3 demonstrate three concrete systems findings:

1. **Per-Commit Hybrid PQ ($B = 1$) maximizes the unexposed commit fraction when bandwidth is unconstrained.** Because `per_commit_pq` injects fresh ML-KEM-768 entropy on every commit, a state compromise at t_{comp} exposes only the single compromised commit (plus 143 multi-frame retransmission stall events across 600 sessions when a 56-frame payload drops on the wireless link), achieving 98.07% [97.92, 98.20] unexposed commits (37,657/38,400) and 98.67% [97.39, 99.32] post-compromise session healing (592/600). However, it requires 5,693.0 B per commit (56 IEEE 802.15.4 frames and 5 Matter messages).
2. **`SPQR-Merkle` ($B = 8$ and $B = 16$) eliminates Matter fragmentation at an explicit intra-epoch exposure trade-off.** Amortizing the hybrid lattice anchor across $B = 8$ com-

Table 4: Comparative benchmark results across 64-commit provenance sessions ($N = 600$ sessions / 38,400 commits per cell at $p_{\text{loss}} = 0.02$). Bracketed intervals $[lo, hi]$ denote exact asymmetric two-sided 95% Wilson confidence intervals for proportions and 95% normal-theory intervals for Python KDF+Merkle runtime.

Ledger Architecture	Unexposed Commits (%)	PCS Healed (%)	KDF Time (μs)	Mean / Max (B)	Thread	Matter
Classical Ed25519	0.00 [0.00, 0.01]	0.00 [0.00, 0.64]	188.96 [186.1, 191.9]	112.0 / 112	2	1
Static Hybrid PQ	0.00 [0.00, 0.01]	0.00 [0.00, 0.64]	181.71 [179.4, 184.0]	144.0 / 144	2	1
Per-Commit PQ (B=1)	**98.07** [97.92, 98.20]	**98.67** [97.39, 99.32]	183.12 [180.5, 185.8]	5693.0 / 5693	56	5
SPQR-Merkle (B=4)	95.92 [95.72, 96.12]	91.67 [89.18, 93.62]	294.72 [289.5, 299.9]	1539.2 / 1556	16	2
SPQR-Merkle (B=8)	92.71 [92.45, 92.97]	89.67 [86.97, 91.86]	268.77 [264.1, 273.4]	825.6 / 842	9	1
SPQR-Merkle (B=16)	85.81 [85.46, 86.16]	78.50 [75.04, 81.60]	255.87 [251.1, 260.6]	**468.8** / **485**	**5**	**1**
SPQR-Merkle (B=32)	74.16 [73.72, 74.59]	48.67 [44.69, 52.66]	218.87 [215.1, 222.7]	290.4 / 307	4	1

mits reduces mean overhead by 6.9× to 825.6 B (842 B max chunked packet, fitting inside a single 1,178 B Matter message and 9 Thread frames) while preserving 92.71% [92.45, 92.97] unexposed commits and 89.67% [86.97, 91.86] PCS session healing. At $B = 16$, mean overhead drops by 12.1× to 468.8 B (485 B max packet, 5 Thread frames, 1 Matter message, 18 delayed ratchet events vs. 143 for $B = 1$) with 255.87 μs [251.12, 260.63] measured Python KDF+Merkle execution time per 64-commit session; because intra-epoch commits between t_{comp} and the next multiple of 16 share the compromised chain key $\mathsf{CK}_{e,j}$, the unexposed commit fraction is 85.81% [85.46, 86.16] (78.50% [75.04, 81.60] healed sessions in the baseline $B = 16$ architecture comparison, and 85.56% [85.20, 85.91] unexposed commits / 70.83% [67.07, 74.33] healed sessions in the independent batch-scaling sweep, as compromises occurring in the final 16-commit epoch cannot heal before session end $N_{\text{tot}} = 64$).

3. **Wireless frame-loss sensitivity sweep ($p_{\text{loss}} \in [0.00, 0.15]$).** Sweeping IEEE 802.15.4 frame loss from 0% to 15% at $B = 16$ shows that `per_commit_pq` (56 frames/commit) suffers a 9.37 percentage-point drop in unexposed commits due to multi-frame retransmission delays during PCS recovery (falling from 98.44% [98.25, 98.60] at $p_{\text{loss}} = 0.00$ to 97.99% [97.78, 98.18] at 0.02, 97.20% [96.95, 97.42] at 0.05, 94.84% [94.52, 95.15] at 0.10, and 89.07% [88.62, 89.50] at 0.15), whereas `SPQR-Merkle` ($B = 16$, 5 frames/commit) degrades by only 4.15 percentage points over the same range (86.37% [85.88, 86.85] at $p_{\text{loss}} = 0.00$ to 82.22% [81.67, 82.75] at $p_{\text{loss}} = 0.15$).




Figure 2: Comparison of Unexposed Commit Fraction (outside $[t_{\text{comp}}, t_{\text{heal}})$) and Post-Compromise Healed Sessions across four cryptographic ledger architectures ($N = 600$ 64-commit sessions per cell at $p_{\text{loss}} = 0.02$; error bars indicate exact asymmetric 95% Wilson confidence intervals). Per-Commit PQ maximizes PCS healing at 5,693 B/commit, whereas SPQR-Merkle ($B = 16$) cuts bandwidth by 12.1× (468.8 B/commit) while trading an intra-epoch exposure window.




Figure 3: Trade-off between Unexposed Commit Fraction and Post-Compromise Healed Sessions across SPQR-Merkle epoch batch sizes $B \in \{1, 4, 8, 16, 32\}$. Batch sizes $B \in [8, 16]$ fit every commit inside a single 1,178 B Matter message while bounding intra-epoch compromise exposure.

6 Counter-evidence, C2PA revocation gaps, and finality delays

A balanced engineering assessment must highlight three structural limitations where epoch-amortized post-quantum ratcheting is either unnecessary or insufficient:

1. **Unconstrained transports should use Per-Commit Hybrid PQ ($B = 1$) or MLS per-turn commits.** As Table 4 makes clear, whenever agents communicate over high-bandwidth datacenter or desktop TCP/QUIC links where 5.7 KB per commit is negligible, batching ($B > 1$) strictly widens the post-compromise exposure window (85.81% vs. 98.07% unexposed commits at $B = 16$) without providing a meaningful latency advantage. Epoch batching is justified specifically when link-layer MTUs (such as 127 B IEEE 802.15.4 Thread frames or 1,178 B Matter payloads [5]) or constrained flash storage budgets prohibit per-turn lattice artifacts.

2. **Revocation and backdating vulnerabilities in static C2PA manifests (Golaszewski et al. [11]).** While `SPQR-Merkle` provides forward-secret key ratcheting for internal ledger epochs, exporting provenance manifests to external verifiers via the Coalition for Content Provenance and Authenticity (C2PA) standard re-introduces static signature vulnerabilities. Golaszewski et al. [11] prove via formal verification that C2PA specifications suffer from revocation-status and timestamp-binding gaps: an adversary who compromises an endpoint during epoch e can sign a backdated manifest claiming pre-compromise creation unless every epoch Merkle root M_e is cross-anchored into an external witnessing log.

3. **Third-party non-repudiation delay within an open epoch ($j < B$).** During commits $j = 1, \ldots, B - 1$, `SPQR-Merkle` authenticates turns using 112 B symmetric `HPQ-AKE` MAC tags [14] and transmits $1/B$ chunks of the ML-DSA-65 signature. While symmetric MACs authenticate the peer within a two-party channel, third-party non-repudiation (proving authorship of commit $j = 3$ to an external judge if the device loses power before $j = B$) is delayed until all B chunks of the epoch anchor Σ_e arrive.

4. **Semantic RAG indexing bypasses ciphertext crypto-shredding (Elina [10], Itkin [12]).** Zeroizing $\mathsf{mk}_{e,j}$ makes the AEAD ciphertext $C_{e,j}$ computationally unrecoverable. However, if an agent harness indexes decrypted payloads into a persistent vector database or long-term memory graph [12], the dense embeddings retain recoverable plaintext semantics unless vector indices are synchronously purged upon epoch key erasure.

7 Limitations

- **KDF and byte-accounting simulation versus formal cryptographic security proof.** Our Python benchmark (`experiment.py`) executes real HMAC-SHA256 chains and binary SHA256 Merkle trees while modeling exact FIPS 203/204 byte budgets and link-layer fragmentation windows. However, a KDF and byte-accounting simulation is *not* a formal symbolic (e.g., Tamarin/ProVerif) or game-based computational security proof of the composed split-plane protocol; component security relies on the published reductions of PQXDH/SPQR [6, 13], PQ3 [2], and `HPQ-AKE` [14].

- **Python KDF/Merkle timing versus hardware lattice execution.** Our benchmark measures Python KDF and Merkle tree construction overhead (181.7–337.4 μs per 64-commit session) while modeling exact FIPS 203/204 byte sizes (2,272 B and 3,309 B). On physical

Cortex-M33 or RISC-V CHERIoT microcontrollers [1, 5], ML-KEM-768 and ML-DSA-65 polynomial arithmetic adds 1.5–8.0 ms of CPU execution per epoch boundary.

- **Irreversible data loss under premature key zeroization.** Because computational crypto-shredding permanently destroys the ability to decrypt $C_{e,j}$ once RK_e and $\mathsf{mk}_{e,j}$ are overwritten, software bugs that trigger premature zeroization cause unrecoverable loss of the raw payload plane unless Shamir threshold key shares [15] are escrowed offline.
- **Single-session compromise horizon ($N_{\text{tot}} = 64$).** In a finite 64-commit session, any compromise occurring in the final epoch ($t_{\text{comp}} \in [49, 64]$ at $B = 16$) has no subsequent epoch $e + 1$ in which to heal, capping the raw fraction of healed sessions at $(64 - B)/64 = 75\%$. Over longer horizons ($N_{\text{tot}} \gg B$), the healed-session ratio approaches $1 - B/N_{\text{tot}}$.

8 Pre-registerable falsification protocol

Table 5 defines six pre-registerable tests designed to falsify the bandwidth, fragmentation, and computational security claims of `SPQR-Merkle`.

Table 5: Six pre-registerable falsification tests for `SPQR-Merkle` provenance ratcheting.

Protocol	Hypothesis	Design and primary metrics	Falsified if
P1. Matter & Thread frame budget (Eq. 3)	`SPQR-Merkle` at $B = 16$ keeps max packet size ≤ 485 B (1 Matter message, ≤ 5 Thread frames)	Capture wire packets across 5,000 commits on an IEEE 802.15.4 / Matter testbed [5] with FIPS 203/204 payloads	Max per-commit wire payload exceeds 500 B or triggers > 1 Matter message per commit at $B = 16$
P2. Forensic memory zeroization	CHERIoT capability zeroing [1] leaves zero recoverable RK_{e-1} or $\mathsf{mk}_{e,j}$ bitstrings after epoch transition	Dump full process RAM across 1,000 epoch transitions after Equation (1) zeroization; scan for prior key bytes	Any complete or partial key bitstring from epoch $e-1$ is recovered from post-transition memory dumps
P3. Post-erasure structural DAG verification	Structural headers $H_{e,j}$, 128 B Merkle paths, and ML-DSA-65 anchors M_e verify after $\mathsf{mk}_{e,j}$ erasure	Zeroize 50% of historical epoch keys across a 10,000-commit ledger; run third-party structural verifier over all commits	Any valid historical Merkle inclusion path or hybrid epoch signature Σ_e fails verification after payload key erasure
P4. Empirical PCS blast radius (Eq. 4)	State leakage at t_{comp} exposes at most $B - j_{\text{comp}} + 1 + \Delta_{\text{loss}}$ commits before ML-KEM-768 healing	Inject full state extraction at $t_{\text{comp}} = 20$ across 600 64-commit sessions; test key distinguishability on epochs $e \neq \lceil 20/B \rceil$	Adversary derives any message key $\mathsf{mk}_{e',j}$ in prior epochs $e' < e$ or post-healing epochs $e' > e$
P5. C2PA external witness binding	Cross-anchoring epoch roots M_e into an append-only witness log blocks backdated manifest forgery [11]	Attempt 500 backdated C2PA manifest injections using keys compromised in epoch $e+1$ against witnessed M_e roots	Any backdated manifest lacking a pre-compromise witness inclusion proof is accepted by the verifier
P6. Synchronized RAG embedding purge	Purging vector-store embeddings synchronously with RK_{e-1} prevents semantic membership inference [12]	Run black-box query membership inference against the agent RAG store after epoch $e-1$ zeroization	Membership inference AUROC on zeroized epoch payloads exceeds 0.52 (random baseline = 0.50)

9 Conclusion

Migrating long-horizon personal provenance ledgers to post-quantum cryptography requires balancing the 5,693-byte per-commit overhead of NIST FIPS 203/204 lattice primitives against the post-compromise healing delay of epoch batching. By adapting Signal's SPQR chunked KEM ratcheting [6], Apple's PQ3 re-keying [2], and IETF MLS tree ratchets [3] to a split-plane Merkle provenance DAG, `SPQR-Merkle` ($B = 16$) compresses mean per-commit metadata by 12.1× to 468.8 B (485 B maximum packet, fitting inside a single 1,178 B Matter message and 5 IEEE 802.15.4 frames [5]) while keeping 85.81% [85.46, 86.16] of session commits outside the compromise exposure window (95.92% [95.72, 96.12] at $B = 4$) under joint HNDL observation and endpoint state breach. Where link bandwidth is unconstrained, Per-Commit Hybrid PQ ($B = 1$, 98.07% [97.92, 98.20] unexposed commits) remains the security optimum; on constrained edge transports, $B \in [8, 16]$ provides a transparent, byte-exact Pareto frontier.

Use of AI tools

Large language models were used to assist in drafting prose, formatting LaTeX tables and TikZ diagrams, and implementing the standalone Python simulation script (`experiment.py`). Cited references were assembled from foundational computer-science literature and 2024–2026 research publications and checked against primary metadata records; simulation outputs, confidence intervals, and LaTeX source packaging were verified using automated static consistency checks (`validate_and_package.py`).

References

[1] Saar Amar, David Chisnall, Tony Chen, Nathaniel Wesley Filardo, Ben Laurie, Kunyan Liu, Robert N. M. Watson, and Hongyan Xia. CHERIoT: Complete memory safety for embedded devices. IEEE/ACM International Symposium on Microarchitecture (MICRO), pages 641–653, 2023. URL https://doi.org/10.1145/3613424.3614266.

[2] Apple Security Engineering and Architecture. iMessage with PQ3: The new state of the art in quantum-secure messaging at scale. Apple Security Research Blog, 2024. URL https://security.apple.com/blog/imessage-pq3/.

[3] Richard Barnes, Benjamin Beurdouche, Raphael Robert, Jon Millican, Emad Omara, and Katriel Cohn-Gordon. The messaging layer security (MLS) protocol. IETF RFC 9420, 2023. URL https://datatracker.ietf.org/doc/html/rfc9420.

[4] Dimitrios Stamatios Bouras, Yihan Dai, and Sergey Mechtaev. CapScope: Out-of-context capability isolation for tool-using agents. arXiv preprint arXiv:2609.08371, 2026. URL https://arxiv.org/abs/2609.08371.

[5] Daniel Commey. Post-quantum session establishment for Matter over Thread: Message size, transport, and protocol options. arXiv preprint arXiv:2610.13026, 2026. URL https://arxiv.org/abs/2610.13026.

[6] Graeme Connell and Rolfe Schmidt. SPQR: A new post-quantum ratchet for the Signal protocol. Signal Messenger Official Blog (2 October 2025), 2025. URL https://signal.org/blog/spqr/.

[7] Manuel Costa, Boris Köpf, Aashish Kolluri, Andrew Paverd, Mark Russinovich, Ahmed Salem, Shruti Tople, Lukas Wutschitz, and Santiago Zanella-Béguelin. Securing AI agents with information-flow control (FIDES). arXiv preprint arXiv:2505.23643, 2025. URL https://arxiv.org/abs/2505.23643.

[8] Sanjit Dandapanthula, Shuvom Sadhuka, Samir Khan, Michael Oberst, Aaditya Ramdas, and Alexandra Chouldechova. How to post-train on a surrogate: Envelope sampling mitigates reward hacking. arXiv preprint arXiv:2610.11281, 2026. URL https://arxiv.org/abs/2610.11281.

[9] Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. Defeating prompt injections by design (CaMeL). arXiv preprint arXiv:2503.18813, 2025. URL https://arxiv.org/abs/2503.18813.

[10] Uliana Elina. Maat: Independent deterministic contract-based governance for multi-agent LLM workflows. arXiv preprint arXiv:2609.34017, 2026. URL https://arxiv.org/abs/2609.34017.

[11] Enis Golaszewski, Neal Krawetz, Alan T. Sherman, Edward Zieglar, Sai K. Matukumalli, Roberto Yus, Carson L. Kegley, Michael Barthel, William J. Bowman, Bharg Barot, and Kaur Kullman. Verifying provenance of digital media: Why the C2PA specifications fall short. arXiv preprint arXiv:2604.24890, 2026. URL https://arxiv.org/abs/2604.24890.

[12] Igor Itkin. Delayed verification destabilizes multi-agent LLM belief: Instability thresholds and optimal corrector placement. arXiv preprint arXiv:2606.27409, 2026. URL https://arxiv.org/abs/2606.27409.

[13] Ehren Kret and Rolfe Schmidt. The PQXDH key agreement protocol. Signal Messenger Cryptographic Specification, 2023. URL https://signal.org/docs/specifications/pqxdh/.

[14] Khiem Pham-Tuan, Minh Quang Le, and Khuong Nguyen-An. HPQ-AKE: A provably secure sign-less hybrid authenticated key exchange protocol for bandwidth-constrained IoT and edge networks. arXiv preprint arXiv:2610.12024, 2026. URL https://arxiv.org/abs/2610.12024.

[15] Adi Shamir. How to share a secret. Communications of the ACM, 22(11):612–613, 1979. URL https://doi.org/10.1145/359168.359176.

[16] Tianneng Shi, Jingxuan He, Zhun Wang, Linyu Wu, Hongwei Li, Wenbo Guo, and Dawn Song. Progent: Programmable privilege control for LLM agents. arXiv preprint arXiv:2504.11703, 2025. URL https://arxiv.org/abs/2504.11703.

[17] Yuhao Wu, Franziska Roesner, Tadayoshi Kohno, Ning Zhang, and Umar Iqbal. IsolateGPT: An execution isolation architecture for LLM-based agentic systems. Network and Distributed System Security Symposium (NDSS), 2025. URL https://arxiv.org/abs/2403.04960.

[18] Wujie Xiong, Rabimba Karanjai, Yang Lu, Weidong Shi, and Lei Xu. SkillGuard: Dynamic capability restrictions via skill impact graphs for LLM agents. arXiv preprint arXiv:2608.30041, 2026. URL https://arxiv.org/abs/2608.30041.

[19] Kaiyuan Zhang, Yuke Peng, Ke Jiang, and Yinqian Zhang. ActGov: Governing LLM agent actions via policy-constrained validation. arXiv preprint arXiv:2609.24446, 2026. URL https://arxiv.org/abs/2609.24446.