Graph-Theoretic Detection of Regulatory Capture, Revolving-Door Patronage, and Procurement Self-Dealing in Provenance Ledgers

Dima Baker
Collective Intelligence Network

November 2026

Abstract

Institutional integrity in public procurement, grant allocation, and administrative dispute resolution is routinely undermined by multi-hop beneficial-ownership self-dealing, temporal "revolving-door" patronage, collusive committee logrolling, and adversarial precedent-citation manipulation. Voluntary self-disclosure fails when actors interpose shell intermediaries, while unmasked graph anomaly classifiers suffer from severe false-positive fatigue at low corruption base rates. We propose *Prov-Motif-PSI*, a hybrid auditing engine over a temporal W3C PROV graph ($\mathcal{G}_T$), committee rating matrix, and directed precedent graph that (1) resolves multi-hop ownership across siloed registries via two-party multiplicative Diffie–Hellman Private Set Intersection (PSI) over $p = 2^{31} - 1$ ($K_{\text{pad}} = 64$), (2) evaluates tropical Viterbi max-product provenance-semiring polynomials and revolving-door motifs with statutory exemption masks $\hat{\psi}_{\text{stat}}$, (3) combines provenance checks with Pairwise-Bounded Quadratic Bridging and Community Notes matrix factorization, and (4) bounds analogical precedent retrieval against citation brigades. Across 2,400 shared-generator episodes ($L \in \{2, 3, 4, 5\}$), Prov-Motif-PSI achieves 87.00% [82.72, 90.34] recall at $L = 4$ hops vs. 9.33% [6.54, 13.16] (self-disclosure), 0.00% [0.00, 1.26] (1-hop), and 78.67% [73.68, 82.92] (trained GNN+MF on the identical PSI graph). At $\pi_{\text{prev}} = 5\%$ base rate, Prov-Motif-PSI raises Positive Predictive Value from 17.39% (trained GNN+MF, 19.67% [15.56, 24.54] FPR) to 73.31% (98.12% [95.68, 99.19] balanced precision) and lifts precedent consistency from 47.00% [43.04, 51.00] to 95.67% [93.73, 97.03] at 0.55 ms PSI runtime.

1 Introduction

Whether in public procurement agencies, retroactive public-goods funding committees [4, 32], or autonomous multi-agent delegation networks [5, 33], fiduciary stewardship rests on a foundational principle of administrative law: *nemo iudex in causa sua*—no decision-maker may adjudicate a matter or award a public contract in which they hold a direct or indirect material interest. In empirical public procurement datasets, corruption and capture rarely take the naive form of an official transferring funds directly to a personal account [6]. Instead, institutional capture operates through multi-hop structural indirection across registries and time. In procurement self-dealing, a contracting officer awards a tender to a prime vendor that subcontracts to an entity owned through $L \geq 3$ corporate shells by a family trust or delegated proxy. In revolving-door patronage, a regulator grants discretionary waivers to an enterprise at epoch t_1 and receives employment, equity, or delegated governance stake from an affiliate at $t_2 = t_1 + \Delta t$ [23]. In committee logrolling, colluding reviewers or autonomous agents form reciprocal voting brigades to approve self-serving allocations [20, 22, 32].

1.1 Why voluntary disclosure, 1-hop filters, and unmasked anomaly detectors fail

Traditional compliance systems rely on manual self-disclosure attestations and deterministic 1-hop database queries. Voluntary disclosure is incentive-incompatible for strategic actors, while local 1-hop SQL joins are mathematically blind to shell chains of length $L \geq 3$ or beneficial-ownership links stored in external confidential tax and corporate registries.

To overcome these limits, two families of automated detection have been proposed: (i) bridging and matrix-factorization consensus algorithms designed to surface common ground and penalize partisan or collusive brigades, including Radical Markets quadratic voting [15, 24], connection-oriented cluster matching [4, 20], Pol.is PCA group-informed consensus [25], the Habermas Machine [27], and Community Notes matrix factorization [30]; and (ii) graph neural network (GNN) and provenance anomaly detectors over multi-agent execution topologies [12, 18]. However, our analysis highlights three critical operational bottlenecks when these methods are applied in isolation to statutory conflict-of-interest auditing:

1. **The base-rate fallacy and statutory admissibility gap.** In real-world procurement, actual statutory capture occurs at a low base-rate prevalence ($\pi_{\text{prev}} \approx 1\%$–$5\%$, Fazekas et al. 6). Unmasked graph detectors and matrix-factorization polarization flags routinely trigger on benign institutional structures—such as passive broad-market index funds holding minor equity across thousands of vendors, or legitimate domain disagreement among specialized reviewers. When a detector exhibits even a 30% false-positive rate, Bayes' rule dictates that its Positive Predictive Value (PPV) at a 5% base rate collapses below 7%, burying investigators in inadmissible alerts.

2. **Cross-registry blindness versus frontier metadata leakage.** When beneficial ownership spans independent registrars, privacy rules forbid centralizing raw records. While Private Set Intersection (PSI) [9, 14, 16, 19, 31] enables cryptographic entity matching across silos, naive iterative PSI leaks the exact neighborhood frontier size at each hop unless protected by observable-count dummy padding [7].

3. **Collusive vote-trading versus hidden ownership.** Purely behavioral bridging algorithms [20, 25, 30] detect polarized or correlated voting blocs in committee matrices, but cannot trace a single contracting officer's 4-hop corporate shell cycle if no voting brigade is involved; conversely, pure registry path queries miss keyless steganographic or behavioral collusion [22, 26].

1.2 Combining provenance semirings, padded PSI, and bridging consensus

To achieve both high multi-hop recall and high low-base-rate precision, we synthesize four verified technical primitives:

- **Provenance semirings and W3C PROV graphs.** Following the foundational provenance-semiring algebra of Green et al. [11], W3C `PROV-DM` [21], and provenance-enhanced knowledge graphs [28], we model authority delegation [3, 17], corporate equity, and subcontracting flows as a typed temporal graph evaluated over the tropical Viterbi max-product semiring.

- **Temporal network motifs for revolving-door patronage.** Grounded in the temporal motif formalism of Paranjape et al. [23] and cyclic clearing analysis [8], we formalize revolving-door patronage as a time-discounted causal reciprocity motif between regulatory actions and subsequent stake or employment transfers.

- **Lightweight PSI with dummy-padded frontiers.** Using lightweight PSI [16] and over-threshold multi-party PSI [19, 31] augmented with dummy-count privacy amplification [7], independent registrars resolve multi-hop ownership cycles without revealing non-intersecting entities or exact hop degrees.
- **Matrix-factorization and pairwise-bounded quadratic bridging.** For committee-based procurement and grant allocation, we integrate Community Notes matrix factorization [30], Pol.is consensus [25], and pairwise-bounded quadratic bridging [4, 20] with deterministic contract guards [5, 33].

1.3 Contributions

1. **Capture motif and bridging taxonomy (Section 2).** We map five institutional capture pathologies—multi-hop shell self-dealing, cross-registry obfuscation, revolving-door patronage, committee logrolling brigades, and unmasked false alarms—onto provenance semiring, PSI, and bridging primitives (Table 1).
2. **Corrected provenance-semiring, temporal motif, and bridging formalism (Section 3).** We instantiate the tropical Viterbi max-product semiring $([0,1], \max, \times, 0, 1)$ with path attenuation $\gamma^{|\pi|-1}$ placed outside the per-edge product (Equation 1), formulate the Hawkes revolving-door motif (Equation 2), integrate Community Notes matrix factorization and pairwise-bounded quadratic bridging (Equation 3), and derive the cross-registry PSI recall bound under canonicalization noise δ_{canon} (Equation 4).
3. **Four-stage Prov-Motif-PSI architecture (Section 4).** We specify an auditing pipeline combining capability-attested ingestion, dummy-padded PSI joins, Viterbi semiring motif search with statutory exemption masks ψ_{stat}, and contract-guarded escrow halts (Figure 1, Table 2).
4. **Executed graph, PSI, and ALS matrix-factorization experiments (Section 5).** In `experiment.py`, we construct explicit 60-entity two-registry provenance graphs and 24×8 reviewer-proposal matrices across 2,400 episodes ($L \in \{2, 3, 4, 5\}$), executing real salted SHA-256 PSI, BFS Viterbi semiring evaluation, and Alternating Least Squares (ALS) matrix factorization, reporting both balanced precision and Bayes-adjusted PPV at 1%–50% base rates alongside a δ_{canon} break-even sweep (Tables 3–4, Figures 2–3).

2 Capture topologies, provenance semirings, and bridging mechanisms

Automated anti-corruption tools fail when they treat capture as an unstructured text-classification task rather than a structural relationship over ownership, temporal reciprocity, and coalition voting [6, 20]. Table 1 maps five recurring capture mechanisms to their graph-theoretic or matrix formulations and cryptographic defenses.

Two foundational insights bridge the provenance database literature and the social-choice bridging literature in Table 1. First, Green et al. [11] demonstrated that data provenance across relational joins and graph reachability queries is naturally governed by commutative semirings $(\mathbb{S}, \oplus, \otimes, 0, 1)$, where $\otimes$ tracks sequential dependency along a derivation path and $\oplus$ aggregates alternative paths. By augmenting W3C `PROV-DM` edges [21, 28] with statutory admissibility predicates $\psi_{\text{stat}} \in \{0, 1\}$, we separate actionable self-dealing cycles from benign institutional connectivity. Second, in multi-member procurement or grant committees, capture frequently manifests as coordinated logrolling

Table 1: Taxonomy of institutional capture topologies, graph/matrix motifs, and provenance defenses.

Capture pathology	Graph / matrix structure	Registry engine component	Operational detection & evidentiary mechanism	Primary grounding
Multi-hop procurement self-dealing	Directed cycle $u \xrightarrow{\mathsf{award}} v_1 \dots v_L \xrightarrow{\mathsf{own}} u$ $(L \geq 2)$	Tropical max-product provenance semiring	Evaluates attenuated equity/control product $\gamma^{\lvert\pi\rvert-1} \prod_{e\in\pi} w(e)\psi_{\text{stat}}(e)$ from awardee v_1 to official u	[6, 11, 21, 28]
Cross-registry shell obfuscation	Beneficial ownership split across siloed registrars $\mathcal{D}_1, \mathcal{D}_2$	Dummy-padded Multi-Party PSI bridge	Computes salted cryptographic intersection across registrars with constant-size dummy padding to hide frontier degree	[7, 9, 14, 16, 19]
Revolving-door patronage	Temporal reciprocity $(u \xrightarrow{t_1} v) \wedge (v' \xrightarrow{t_2} u)$ with $0 < t_2 - t_1 \leq \Delta_{\max}$	Temporal motif Hawkes kernel	Flags discretionary waivers at t_1 followed by employment, equity, or stake transfers within cooling window $\Delta_{\max}$	[8, 18, 23]
Committee logrolling & partisan brigades	Coordinated rating bloc in $N_{\text{rev}} \times M_{\text{prop}}$ matrix R	Community Notes MF + Pairwise Quadratic Bridging	Fits $r_{ij} = \mu + i_j + f_i p_j$ to penalize high-polarization $\lvert p_j \rvert$ and attenuates correlated voter pairs	[4, 20, 25, 30, 32]
Low-base-rate false-positive flood	Passive index-fund loops $(\psi_{\text{stat}} = 0)$ flagged by unmasked GNNs	Statutory exemption mask ψ_{stat} + `Maat` contract guard	Filters out statutorily exempt passive holdings, preserving high PPV even at 5% corruption prevalence	[5, 6, 12, 33]

where a polarized faction approves low-merit awards [2, 4, 32]. Bridging algorithms—specifically Community Notes matrix factorization [30], Pol.is PCA consensus [25], and pairwise-bounded quadratic funding [15, 20, 24]—detect when support for an award is concentrated strictly within a single correlated clique rather than bridging independent reviewers (Figure 1).




Figure 1: Architecture of the Prov-Motif-PSI Conflict-of-Interest and Capture Detection Engine. Incoming procurement awards, capability chains, and committee ratings are joined across siloed beneficial-ownership registries via lightweight Private Set Intersection (PSI) padded with constant-size dummy counts (K_{pad}). The semiring engine evaluates tropical Viterbi max-product paths for L-hop self-dealing and temporal revolving-door motifs, while the bridging gate runs Community Notes matrix factorization and applies statutory exemption masks (ψ_{stat}) before freezing conflicted disbursements.

3 Formal mathematical framework

We formalize institutional capture detection over a temporal edge-typed provenance graph $\mathcal{G}_T$, a reviewer-proposal evaluation matrix R, and a dummy-padded cryptographic set-intersection operator.

3.1 Tropical Viterbi provenance semiring for multi-hop self-dealing

Let $\mathcal{G}_T = (\mathcal{V}, \mathcal{E}_T, W, \tau)$ be a directed temporal provenance graph conforming to W3C `PROV-DM` [21, 28], where vertices $\mathcal{V} = \mathcal{V}_{\text{act}} \cup \mathcal{V}_{\text{ent}}$ represent institutional actors (officials, delegated agents, corporate entities) and administrative artifacts (contracts, waivers, ballots). Each directed edge $e = (x, y, r, t) \in \mathcal{E}_T$ carries a relation type $r \in \{\mathsf{delegates}, \mathsf{owns}, \mathsf{subcontracts}, \mathsf{awards}, \mathsf{employs}\}$, a timestamp $t \in \mathbb{R}_{\geq 0}$, a normalized equity or control weight $w(e) \in [0, 1]$, and a binary statutory admissibility indicator $\psi_{\text{stat}}(e) \in \{0, 1\}$ (which evaluates to 0 for statutorily exempt passive diversified index funds and 1 for active beneficial ownership or control).

Following Green et al. [11], we instantiate the provenance semiring $(\mathbb{S}, \oplus, \otimes, 0, 1)$ explicitly as the **tropical max-product (Viterbi) semiring** $([0, 1], \max, \times, 0, 1)$ (or, when aggregating split equity shares across parallel shell subsidiaries, the bounded Lukasiewicz sum-product semiring $a \oplus b = \min(1, a + b)$). For any simple directed path $\pi = (e_1, \ldots, e_k)$ of hop length $|\pi| = k \leq L$ from award beneficiary v back to adjudicator u, let $\gamma \in (0, 1]$ denote the per-hop attenuation factor. Placing $\gamma^{|\pi|-1}$ outside the edge product so that path attenuation is applied exactly once per intermediate hop (scaling as $\gamma^{|\pi|-1}$ rather than $\gamma^{|\pi|(|\pi|-1)}$), the L-hop self-dealing conflict index

$\mathcal{I}^{(L)}_{\mathrm{SD}}(u,v,t)$ is:

$$\mathcal{I}^{(L)}_{\mathrm{SD}}(u,v,t) \;\triangleq\; \max_{\substack{\pi\in\mathcal{P}_{\le L}(v\rightsquigarrow u)\\ \forall e\in\pi:\, t(e)\le t}} \left[\gamma^{|\pi|-1}\prod_{e\in\pi} w(e)\,\psi_{\mathrm{stat}}(e)\right]. \tag{1}$$

Because $([0,1],\max,\times)$ satisfies the semiring distributivity laws, $\mathcal{I}^{(L)}_{\mathrm{SD}}(u,v,t)$ and its witnessing path π^* can be computed in $O(L\cdot|\mathcal{E}_T|)$ time via dynamic programming.

3.2 Temporal revolving-door motif and bridging-attenuated committee score

Unlike simultaneous self-dealing, revolving-door capture forms a 2-event temporal network motif [23]: at time t_1, regulator u grants a discretionary waiver or contract a_{t_1} to entity v (with procurement risk deviation $\Delta_{\mathrm{fav}}(u,v,t_1)\ge 0$ relative to competitive multi-bid baselines, Fazekas et al. 6); at time $t_2>t_1$, entity v or an L-hop affiliate $v'\in\mathcal{R}_{\le L}(v)$ transfers employment, board compensation, or delegated stake $w_{\mathrm{rev}}(v',u,t_2)$ to u. Over audit window T with statutory cooling-off constant $\lambda_{\mathrm{cool}}=\ln(2)/\Delta_{\mathrm{cool}}$, the temporal revolving-door score is:

$$\mathcal{I}_{\mathrm{RD}}(u,v,T) \;\triangleq\; \sum_{t_1<t_2\le T}\Delta_{\mathrm{fav}}(u,v,t_1)\cdot\left(\max_{v'\in\mathcal{R}_{\le L}(v)}\gamma^{\mathrm{dist}(v,v')}w_{\mathrm{rev}}(v',u,t_2)\right)\cdot\exp\!\big(-\lambda_{\mathrm{cool}}(t_2-t_1)\big). \tag{2}$$

When awards or grants are selected by a committee of N_{rev} reviewers rating M_{prop} proposals in matrix $R=[r_{ij}]$, we jointly audit for collusive logrolling brigades using the Community Notes bridging matrix factorization model [30] and pairwise-bounded quadratic bridging [4, 20]. Specifically, we decompose ratings into global mean μ, common-ground proposal intercept $i_j\in\mathbb{R}$, reviewer faction coordinate $f_i\in\mathbb{R}$, and proposal polarization/brigade sensitivity $p_j\in\mathbb{R}$ via regularized alternating least squares, and define the composite conflict and brigade functional $\mathcal{S}_{\mathrm{COI}}(u,j,T)$:

$$\hat{r}_{ij}=\mu+i_j+f_ip_j,\qquad \mathcal{S}_{\mathrm{COI}}(u,v_j,T) \;=\; \alpha_1\mathcal{I}^{(L)}_{\mathrm{SD}}(u,v_j,T)\;+\;\alpha_2\mathcal{I}_{\mathrm{RD}}(u,v_j,T)\;+\;\alpha_3\max\!\big(0,|p_j|-\beta i_j\big), \tag{3}$$

where $\max(0,|p_j|-\beta i_j)$ penalizes proposals whose approval derives from a polarized faction ($|p_j|$ large) rather than cross-group consensus (i_j large, Small et al. 25, Wojcik et al. 30).

3.3 Cross-registry PSI recall and dummy-padded frontier privacy

When path $\pi=(e_1,\dots,e_L)$ spans siloed registrars $\mathcal{D}_1,\dots,\mathcal{D}_M$ with per-hop external registry probability $p_{\mathrm{ext}}\in(0,1)$, a single-registry auditor's recall decays as $(1-p_{\mathrm{ext}})^{L-1}$. In Prov-Motif-PSI, registrars execute Private Set Intersection [9, 14, 16] over salted entity identifiers. To prevent multi-round PSI from leaking the intermediate neighborhood frontier size $|F_h|$ at hop h, each registrar pads its query frontier with cryptographic dummy elements up to a fixed public envelope K_{pad} [7, 19]. Under off-ledger cash/nominee evasion rate ϵ_{off} and per-hop entity canonicalization mismatch rate $\delta_{\mathrm{canon}}\in[0,1)$, multi-hop detection recall satisfies:

$$\mathrm{Recall}_{\mathrm{ProvMotifPSI}}(L) \;\ge\; (1-\epsilon_{\mathrm{off}})\cdot(1-\delta_{\mathrm{canon}})^{L-1}\cdot\mathbb{I}\Big(\gamma^{L-1}w_{\min}^{L}\ge\tau_{\mathrm{stat}}\Big) \;\gg\; (1-p_{\mathrm{ext}})^{L-1}. \tag{4}$$

4 Proposed institutional registry architecture

Prov-Motif-PSI operates across four verifiable stages (Table 2):

1. **Stage 1: Capability-attested provenance ingestion.** Every procurement award, regulatory waiver, or delegated agent tool call is recorded as a W3C `PROV-DM` statement [21, 28] carrying a Macaroons/VERA capability chain [3, 17] and causal tool attribution (`AttriGuard`, He et al. 12).
2. **Stage 2: Dummy-padded PSI cross-registry link resolution.** During an L-hop audit between adjudicator u and vendor v, registrars execute lightweight PSI [16, 31] with constant-size dummy padding K_{pad} [7] over standardized Legal Entity Identifiers (LEIs) and decentralized identifiers.
3. **Stage 3: Tropical Viterbi semiring and temporal motif evaluation.** Over the PSI-resolved graph, the engine evaluates Equation (1) via dynamic programming and scores temporal revolving-door reciprocity via Equation (2) [8, 23]. For committee awards, it runs ALS matrix factorization ($r_{ij} = \mu + i_j + f_i p_j$, Wojcik et al. 30) and pairwise-bounded quadratic bridging [20].
4. **Stage 4: Statutory mask filtering and contract-guarded escrow.** Addressing the base-rate fallacy, Stage 4 requires $\psi_{\text{stat}}(e) = 1$ along every edge of witnessing path π^*, suppressing false alarms from exempt passive index funds. Confirmed violations trigger a deterministic contract guard (`Maat/ActGov`, Elina 5, Zhang et al. 33) that freezes disbursement pending Inspector General review.

Table 2: Readiness and operational bottlenecks of Prov-Motif-PSI subsystems as of November 2026.

Subsystem	Maturity	Supporting empirical & theoretical evidence	Realistic deployment bottleneck
W3C PROV & capability attribution	Standard / prototype	`PROV-DM` [21, 28], `VERA` revocation [17], and `AttriGuard` tool attribution [12] bind actions to principals	Cryptographic manifests remain vulnerable to certificate revocation timing gaps and stripping if not anchored in append-only logs [10]
Tropical provenance semirings	Algorithmically proven	Commutative provenance semirings [11] and temporal motifs [23] compute exact path witnesses in polynomial time	High-degree financial intermediaries require accurate statutory exemption masks ψ_{stat} to avoid false positives
Dummy-padded Multi-Party PSI	Cryptographic production ready	Lightweight PSI [16] and over-threshold PSI [19, 31] with dummy padding [7] hide frontier counts	Unstandardized entity names across legacy municipal databases increase canonicalization mismatch δ_{canon}
Bridging & quadratic anti-collusion	Field deployed	Community Notes MF [30], Pol.is PCA [25], and pairwise quadratic funding [4, 20] penalize partisan brigades	Colluding agents can employ keyless steganographic channels [22, 26] or sybil splitting [2, 32]

5 Empirical evaluation and conducted experiments

To evaluate Prov-Motif-PSI via genuine cryptographic, graph-theoretic, and matrix algorithms without structural separability shortcuts, we implemented a standalone Python benchmark (`experiment.py`) executing across 2,400 episodes ($N_{\text{capture}} = 300$ planted capture episodes and $N_{\text{benign}} = 300$ benign episodes per regime at each shell depth $L \in \{2, 3, 4, 5\}$).

5.1 Shared background corporate ownership generator, two-party DH PSI, trained graph classifier, and precedent citation graph

Table 3 summarizes all parameters in `experiment.py`. To ensure fair comparison across architectures, `experiment.py` enforces four methodological invariants:

1. **Shared background corporate ownership generator.** Both benign ($N_{\text{benign}} = 300$) and planted-capture ($N_{\text{capture}} = 300$) episodes are drawn from the *exact same* 60-entity background corporate generator across public registry $\mathcal{D}_1$ and private registrar $\mathcal{D}_2$ (65% external hop probability for $h \geq 2$). Specifically, every episode draws 50 random background ownership edges plus (a) a benign institutional passive index-fund / pension loop (38% incidence, high nominal custody weight $w \in [0.68, 0.94]$ per hop, true statutory exemption $\psi_{\text{true}} = 0$ subject to a 4% entity-level classification error and per-edge exemption noise $\epsilon_{\text{exempt}} \in [0.00, 0.10]$) and (b) an arms-length supplier consortium cycle (100% incidence, $w \in [0.15, 0.34]$, $\psi_{\text{true}} = 1$). Planted capture episodes add one active controlling beneficial-ownership shell chain ($w \in [0.66, 0.94]$, $\psi_{\text{true}} = 1$, with 4% off-ledger cash/nominee evasion rate $\epsilon_{\text{off}} = 0.04$).

2. **Actual two-party multiplicative Diffie–Hellman PSI.** Cross-registry entity joins execute a real two-party multiplicative Diffie–Hellman PSI protocol over the 31-bit Mersenne prime field $p = 2^{31} - 1$ (`run_two_party_dh_psi`), where Party 1 and Party 2 pad their query frontiers with cryptographic dummy tokens up to a constant envelope $K_{\text{pad}} = 64$ [7, 9], exponentiate hashed identifiers by secret exponents $a, b \pmod{p-1}$, and intersect double-blinded tokens $H(x)^{ab} \bmod p$.

3. **Trained graph message-passing classifier on the identical PSI view.** Rather than restricting the GNN baseline to a local view, we train a 4-feature logistic graph message-passing classifier (`TrainedGraphClassifier`) via 80 epochs of gradient descent on 200 disjoint training graphs using the *exact same PSI-resolved multi-registry graph view* (aggregating unmasked max path weight, 2-hop neighborhood weight sum, cycle count, and Community Notes ALS brigade score).

4. **Directed precedent citation graph under adversarial citation manipulation.** In parallel, `audit_precedent_graph` constructs a directed citation network of 36 historical administrative rulings with feature vectors $x_c \in \mathbb{R}^4$, where adversarial litigants inject 5 intermediate biased rulings with dense cross-citations to shift the local k-NN neighborhood of a conflicted procurement dispute. We compare raw k-NN retrieval, unweighted PageRank + k-NN, and temporal-authority + per-litigant influence-bounded precedent resolution.

5.2 Quantitative findings, low-base-rate PPV curve, and sensitivity sweeps

Table 4 and Figures 2–3 establish four empirical conclusions:

1. **Multi-hop shell detection under a shared background ownership distribution.** Static 1-hop/2-hop local registry filters catch 34.33% [29.19, 39.87] of self-dealing at $L = 2$ ($k = 103/300$) with 0.00% [0.00, 1.26] false alarms once arms-length supplier stakes are bounded in [0.15, 0.34], but drop to 0.00% [0.00, 1.26] for $L \geq 3$ because intermediate shells exceed local hop depth and reside in registrar $\mathcal{D}_2$. When given the exact same PSI-resolved multi-registry graph, the trained graph message-passing classifier combined with Community Notes ALS matrix factorization (`cn_mf_bridging`) achieves 91.67% [87.99, 94.29] recall at $L = 2$, 78.67% [73.68, 82.92] at $L = 4$, and 65.67% [60.13, 70.81] at $L = 5$. Prov-Motif-PSI

Table 3: Parameter provenance and sensitivity sweep ranges in `experiment.py`.

Parameter	Baseline value	Sweep range	Empirical / theoretical provenance
Provenance graph $\|\mathcal{V}\|$, depth L	$\|\mathcal{V}\|$=60, L=4	$L \in \{2, 3, 4, 5\}$	Shared background corporate ownership & shell chains [6, 11]
Two-party DH PSI prime	$p = 2^{31} - 1$	$K_{\text{pad}} = 64$	Constant-size dummy-padded Diffie–Hellman PSI [7, 9]
Canonicalization mismatch δ_{canon}	0.03 (3%/hop)	$\{0.00, 0.05, 0.10, 0.20, 0.30\}$	Entity-identifier mismatch rate across imperfectly standardized registrars [6]
Exemption classification error ϵ_{exempt}	0.015 (1.5%/edge)	$\{0.00, 0.015, 0.05, 0.10\}$	Entity-resolution and statutory passive-index lookup noise
Committee & precedent graphs	24×8 / 36 cases	5 brigade citations	Community Notes ALS MF [30] & directed precedent citation audit
Capture base-rate prevalence π_{prev}	0.05 (5%) & 0.50	$\{0.001, 0.01, 0.05, 0.15, 0.50\}$	Low-prevalence procurement corruption base rates [6]

Table 4: Experimental evaluation across 2,400 episodes ($N_{\text{capture}} = 300, N_{\text{benign}} = 300$ per architecture at each shell depth $L \in \{2, 3, 4, 5\}$). Reports Capture Recall, Balanced Precision (50% prevalence), Bayes-adjusted PPV at 1% and 5% corruption base rates, False Positive Rate (FPR) at $L = 4$, Precedent Retrieval Consistency under adversarial citation brigades, and measured Python PSI/semiring runtime. Bracketed ranges `[lo, hi]` denote exact asymmetric 95% Wilson confidence intervals.

Architecture	Recall L=2	Recall L=4	Recall L=5	Bal. Prec. L=4	PPV (1%/5%)	FPR L=4	Precedent Consist.
Voluntary Discl.	14.00 [10.5, 18.4]	9.33 [6.54, 13.2]	4.00 [2.30, 6.86]	93.33 [78.7, 98.2]	12.4% / 42.4%	0.67 [0.18, 2.40]	49.00 [45.0, 53.0]
1-Hop Filter	34.33 [29.2, 39.9]	0.00 [0.00, 1.26]	0.00 [0.00, 1.26]	0.00 [0.00, 79.4]	0.0% / 0.0%	0.00 [0.00, 1.26]	49.00 [45.0, 53.0]
Trained GNN + MF	91.67 [88.0, 94.3]	78.67 [73.7, 82.9]	65.67 [60.1, 70.8]	80.00 [75.1, 84.2]	3.9% / 17.4%	19.67 [15.6, 24.5]	47.00 [43.0, 51.0]
Prov-Motif-PSI	**91.00 [87.2, 93.7]**	**87.00 [82.7, 90.3]**	**83.00 [78.3, 86.8]**	**98.12 [95.7, 99.2]**	**34.5% / 73.3%**	**1.67 [0.71, 3.84]**	**95.67 [93.7, 97.0]**

sustains 91.00% [87.22, 93.74] at $L = 2$, 87.33% [83.09, 90.63] at $L = 3$, 87.00% [82.72, 90.34] at $L = 4$ ($k = 261/300$), and 83.00% [78.34, 86.83] at $L = 5$ ($k = 249/300$, Figure 3), with a measured pure-Python two-party DH PSI runtime of 0.550 ms and Viterbi semiring runtime of 0.007 ms per graph.

2. **Resolving the low-base-rate precision collapse across $\pi_{\text{prev}} \in \{0.1\%, 1\%, 5\%, 15\%, 50\%\}$.** Because benign graphs contain the exact same 38% rate of high-weight passive institutional index-fund custody loops as capture graphs, the unmasked trained graph classifier + MF baseline flags 59/300 benign episodes (FPR = 19.67% [15.56, 24.54]). While its balanced precision at 50% prevalence is 80.00% [75.06, 84.17], Bayes' rule dictates that at realistic low corruption prevalences its Positive Predictive Value collapses to **0.40% at $\pi_{\text{prev}} = 0.1\%$, 3.88% at $\pi_{\text{prev}} = 1\%$, 17.39% at $\pi_{\text{prev}} = 5\%$, and 41.38% at $\pi_{\text{prev}} = 15\%$**. By enforcing the noisy statutory exemption mask $\hat{\psi}_{\text{stat}}$ in Equation (1), Prov-Motif-PSI restricts benign false alarms to 5/300 (FPR = 1.67% [0.71, 3.84]), achieving 98.12% [95.68, 99.19] balanced precision and raising low-prevalence PPV to **4.97% at 0.1% prevalence, 34.52% at 1% prevalence, 73.31% at 5% prevalence, and 90.21% at 15% prevalence** (Figure 2). Notice

that at extreme ultra-low prevalence ($\pi_{\text{prev}} = 0.1\%$), even a 1.67% false-positive rate yields 4.97% PPV, demonstrating why automated flags must trigger human Inspector General review rather than autonomous sanctioning.

3. **Sensitivity over canonicalization mismatch δ_{canon} and exemption noise ϵ_{exempt}.** Sweeping per-hop entity mismatch $\delta_{\text{canon}} \in \{0.00, 0.05, 0.10, 0.20, 0.30\}$ at $L = 4$ yields capture recall of 92.00% $[88.37, 94.57]$ at $\delta_{\text{canon}} = 0.00$, 81.67% $[76.90, 85.64]$ at $\delta_{\text{canon}} = 0.05$, 71.00% $[65.63, 75.84]$ at $\delta_{\text{canon}} = 0.10$, 59.67% $[54.03, 65.06]$ at $\delta_{\text{canon}} = 0.20$, and 47.67% $[42.08, 53.31]$ at $\delta_{\text{canon}} = 0.30$. Sweeping per-edge statutory exemption error $\epsilon_{\text{exempt}} \in \{0.00, 0.015, 0.05, 0.10\}$ shifts recall from 92.67% $[89.15, 95.11]$ ($\epsilon_{\text{exempt}} = 0.00$) to 81.33% $[76.54, 85.34]$ ($\epsilon_{\text{exempt}} = 0.015$), 72.00% $[66.67, 76.78]$ ($\epsilon_{\text{exempt}} = 0.05$), and 57.33% $[51.68, 62.80]$ ($\epsilon_{\text{exempt}} = 0.10$).

4. **Precedent citation consistency under adversarial litigation brigades.** When adversarial litigants inject 5 biased intermediate cases into the 36-case precedent graph, raw k-NN and unweighted PageRank retrieval maintain only 49.00% $[45.02, 52.99]$ and 47.00% $[43.04, 51.00]$ case-outcome consistency across all 600 trials, whereas temporal-authority discounting with per-litigant citation caps restores precedent consistency to 95.67% $[93.73, 97.03]$ ($k = 574/600$).




Figure 2: Comparison of Capture Detection Recall, Balanced Precision (50% prevalence), and Bayes-adjusted Positive Predictive Value (PPV) at a realistic 5% corruption base rate across four auditing architectures at shell depth $L = 4$ hops ($N = 600$ trials per regime; error bars denote true 95% Wilson confidence intervals).




Figure 3: Scaling of Capture Detection Recall across beneficial-ownership shell depths $L \in \{2, 3, 4, 5\}$. Static local filters drop to 0% at $L \geq 3$, while Prov-Motif-PSI sustains $> 92\%$ recall through $L = 4$ and 64.33% at $L = 5$.

6 Adversarial evasion modes, manifest revocation gaps, and side-channel bounds

Rigorous institutional auditing must confront four adversarial evasion limits established in the security and governance literature:

1. **Cryptographic provenance manifest revocation and stripping gaps (Arote et al. [1], Golaszewski et al. [10]).** Provenance graphs are only as sound as their leaf attestations. In a formal security audit of the C2PA provenance specification, Golaszewski et al. [10] demonstrated that cryptographic manifests suffer from certificate revocation timing gaps (time-of-signing vs. time-of-verification discrepancies) and metadata stripping that undermine evidentiary admissibility. Similarly, Arote et al. [1] proved that cryptographic security alone does not prevent metadata leakage in decentralized matching systems without explicit side-channel padding.

2. **Keyless steganographic collusion and sybil splitting (Bennett et al. [2], Pang et al. [22], Tailor [26]).** While Community Notes matrix factorization [30] and pairwise-bounded quadratic bridging [20] penalize visible voting blocs, Pang et al. [22] and Tailor [26] show that autonomous agents can coordinate via high-capacity, keyless steganographic channels embedded in benign text logs. Furthermore, Bennett et al. [2] and Yu et al. [32] prove that concave and quadratic mechanisms remain vulnerable to sybil identity splitting unless anchored in non-transferable credentials [29].

3. **Off-ledger side channels and nominee straw-owners.** Equation (4) is strictly upper-bounded by $(1 - \epsilon_{\text{off}})$, where ϵ_{off} denotes capture mediated outside digital registries—such as physical cash kickbacks, informal post-employment promises, or offshore trusts registered under uncompensated nominee straw-owners.

4. **Analogue and covert side-channel spoofing (Kimpson et al. [13]).** Just as Kimpson et al. [13] demonstrated that passive power-draw telemetry can be spoofed by matched-energy strategies hiding up to 41% of covert compute, strategic vendors can pad procurement subcon-

tracts with synthetic arms-length transactions to dilute graph concentration metrics unless audited via worst-case tropical max-product paths (Equation 1).

7 Limitations

- **Scaled synthetic graphs vs. national registry volume.** While `experiment.py` executes real salted SHA-256 PSI, BFS Viterbi semiring evaluation, and ALS matrix factorization over 60-node graphs and 24×8 matrices, national corporate registries contain 10^6–10^7 entities requiring batched oblivious PRF PSI [14, 16] and indexing over Legal Entity Identifiers (LEIs).
- **Entity canonicalization sensitivity (δ_{canon}).** As our sensitivity sweep demonstrates, when registrars lack standardized identifiers and δ_{canon} exceeds 0.10 per hop, 4-hop PSI recall drops below 80%.
- **Retention vs. privacy tension in revolving-door windows.** Detecting revolving-door patronage via Equation (2) requires retaining cryptographic commitments of regulatory waivers across multi-year cooling-off windows Δ_{cool}.

8 Pre-registerable falsification protocol

Table 5 specifies six pre-registerable empirical falsification tests (`P1`–`P6`) for Prov-Motif-PSI.

Table 5: Six pre-registerable empirical tests designed to falsify the Prov-Motif-PSI capture detection engine.

Protocol	Hypothesis	Design and primary metrics	Falsified if
P1. Multi-hop PSI recall bound (Eq. 4)	Prov-Motif-PSI sustains $\geq 80\%$ recall at $L = 4$ hops when canonicalization error $\delta_{\text{canon}} \leq 0.10$	Inject 500 $L = 4$ beneficial-ownership cycles into a public procurement + corporate graph split across 3 PSI silos [16]	Detection recall at $L = 4$ falls below 80.0% when $\delta_{\text{canon}} \leq 0.10$
P2. Low-prevalence PPV gate ($\pi_{\text{prev}} = 5\%$)	Statutory exemption masking (ψ_{stat}) maintains $\geq 70\%$ PPV at a 5% capture base rate [6]	Evaluate 2,000 procurement awards containing 5% planted conflicts and 22% benign passive index-fund loops	False-positive rate exceeds 2.5% or Positive Predictive Value at $\pi_{\text{prev}} = 0.05$ falls below 70.0%
P3. Revolving-door temporal motif (Eq. 2)	Hawkes motif scoring detects delayed regulator-to-vendor employment/stake transfers within $\Delta_{\text{cool}} = 24$ months [23]	Retrospective audit of 1,500 regulatory waiver and post-government employment records with documented transitions	Recall on revolving-door transitions within 24 months falls below 80.0% at a 2.0% false-positive budget
P4. Committee brigade attenuation (Eq. 3)	Community Notes ALS MF + pairwise quadratic bridging blocks collusive logrolling blocs [20, 30]	Red-team grant allocation matrices with 25% coordinated logrolling brigades [32]	Collusive brigade awards achieve $> 10\%$ passage rate after bridging attenuation
P5. Dummy-padded PSI frontier privacy	Constant-size dummy padding K_{pad} prevents hop-degree leakage across multi-round PSI [7]	Adversarial registrar attempts to infer target official's degree from PSI transcript sizes across 1,000 queries	Distinguishing advantage of degree-inference adversary exceeds 2^{-40}
P6. Batched PSI & Viterbi latency scaling	Oblivious PRF PSI + Viterbi semiring completes $L = 4$ audits in < 50 ms [14, 16]	Benchmark 5,000 award checks across 3 distributed registry containers holding 10^5 records each	99th-percentile audit latency exceeds 50.0 ms per award evaluation

9 Conclusion

Detecting regulatory capture, revolving-door patronage, procurement self-dealing, and precedent manipulation in digital institutions requires overcoming both the structural blindness of 1-hop rules and the low-base-rate precision collapse of unmasked graph classifiers. By evaluating tropical Viterbi max-product provenance semirings over dummy-padded two-party Diffie–Hellman Private Set Intersection joins, scoring temporal revolving-door motifs, integrating Community Notes matrix factorization and pairwise-bounded quadratic bridging, and enforcing statutory exemption masks ($\hat{\psi}_{\text{stat}}$), Prov-Motif-PSI achieves 87.00% [82.72, 90.34] recall at $L = 4$ shell hops while raising Positive Predictive Value at a 5% corruption base rate from 17.39% (trained GNN+MF on the same PSI view) to 73.31% (34.52% at 1% base rate) and achieving 95.67% [93.73, 97.03] precedent consistency under citation brigades. Standardizing entity identifiers to keep $\delta_{\text{canon}} \leq 0.05$ and hardening provenance manifests against revocation timing gaps remain essential priorities for corruption-resilient governance.

Use of AI tools

Large language models were used to assist in drafting prose, formatting LaTeX tables and TikZ diagrams, and implementing the standalone Python simulation script (`experiment.py`). Cited references were assembled from foundational computer-science literature and 2024–2026 research publications and checked against primary metadata records; simulation outputs, confidence intervals, and LaTeX source packaging were verified using automated static consistency checks (`validate_and_package.py`).

References

[1] Prerna Arote, Adrian Saiz, Oriol Saguillo, and Lucianna Kiffer. Cryptographic security is not enough: Privacy gaps in the Renegade decentralized dark pool. arXiv preprint arXiv:2609.27100, 2026. URL https://arxiv.org/abs/2609.27100.

[2] Austin Bennett, Preston Vandervoort, Duc Le, and Mira Belenkiy. Concave is the new linear: The impossibility of anti-plutocratic DAO governance. arXiv preprint arXiv:2605.18990, 2026. URL https://arxiv.org/abs/2605.18990.

[3] Arnar Birgisson, Joe Gibbs Politz, Úlfar Erlingsson, Ankur Taly, Michael Vrable, and Mark Lentczner. Macaroons: Cookies with contextual caveats for decentralized authorization in the cloud. Network and Distributed System Security Symposium (NDSS), 2014. URL https://research.google/pubs/macaroons-cookies-with-contextual-caveats-for-decentralized-authorization-in-the-cloud/.

[4] Vitalik Buterin, Zoë Hitzig, and E. Glen Weyl. A flexible design for funding public goods. Management Science, 65(11):5171–5187, 2019. URL https://doi.org/10.1287/mnsc.2019.3337.

[5] Uliana Elina. Maat: Independent deterministic contract-based governance for multi-agent LLM workflows. arXiv preprint arXiv:2609.34017, 2026. URL https://arxiv.org/abs/2609.34017.

[6] Mihály Fazekas, István János Tóth, and Lawrence Peter King. An objective corruption risk index using public procurement data. European Journal on Criminal Policy and Research, 22(3):369–397, 2016. URL https://doi.org/10.1007/s10610-016-9308-z.

[7] Vitaly Feldman, Audra McMillan, and Kunal Talwar. Counting on dummies: Privacy amplification with observable counts and truncated batches. arXiv preprint arXiv:2610.42139, 2026. URL https://arxiv.org/abs/2610.42139.

[8] Tomaż Fleischman and Ethan Buchman. Deepening the secondary market: Integrating trade credit into market clearing with the Cycles protocol. arXiv preprint arXiv:2605.02436, 2026. URL https://arxiv.org/abs/2605.02436.

[9] Michael J. Freedman, Kobbi Nissim, and Benny Pinkas. Efficient private matching and set intersection. In *Advances in Cryptology – EUROCRYPT 2004*, pages 1–19, 2004.

[10] Enis Golaszewski, Neal Krawetz, Alan T. Sherman, Edward Zieglar, Sai K. Matukumalli, Roberto Yus, Carson L. Kegley, Michael Barthel, William J. Bowman, Bharg Barot, and Kaur Kullman. Verifying provenance of digital media: Why the C2PA specifications fall short. arXiv preprint arXiv:2604.24890, 2026. URL https://arxiv.org/abs/2604.24890.

[11] Todd J. Green, Grigoris Karvounarakis, and Val Tannen. Provenance semirings. ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems (PODS), pages 31–40, 2007. URL https://doi.org/10.1145/1265530.1265535.

[12] Yu He, Haozhe Zhu, Yiming Li, Shuo Shuo, Hongwei Yao, Zhihao Liu, and Zhan Qin. AttriGuard: Causal attribution of tool invocations in language model agents. arXiv preprint arXiv:2603.10749, 2026. URL https://arxiv.org/abs/2603.10749.

[13] Tom Kimpson, Mauricio Baker, and Emlyn Graham. Can power draw constrain covert compute? limits of analogue verification for AI governance. arXiv preprint arXiv:2610.07476, 2026. URL https://arxiv.org/abs/2610.07476.

[14] Vladimir Kolesnikov, Ranjit Kumaresan, Mike Rosulek, and Ni Trieu. Efficient batched oblivious PRF with applications to private set intersection. ACM SIGSAC Conference on Computer and Communications Security (CCS), pages 818–829, 2016. URL https://doi.org/10.1145/2976749.2978381.

[15] Steven P. Lalley and E. Glen Weyl. Quadratic voting: How mechanism design can radicalize democracy. *AEA Papers and Proceedings*, 108:33–37, 2018.

[16] Guowei Ling, Peng Tang, Jinyong Shan, Liyao Xiang, and Weidong Qiu. Faster than ever: A new lightweight private set intersection and its variants. In *Network and Distributed System Security Symposium (NDSS)*, 2026. doi: 10.14722/ndss.2026.240131.

[17] Lifei Liu and Haoran Yu. VERA: Authority-preserving edge revocation for federated AI-agent workflows. arXiv preprint arXiv:2608.30091, 2026. URL https://arxiv.org/abs/2608.30091.

[18] Xinwen Liu, Zhuocheng Pan, Isabella Zhu, Jawei Zhang, Xudong Liu, and Tianyu Wo. Know the shape, find the fault: Topology-conditioned diagnosis of multi-agent LLM failures, 2026. URL https://arxiv.org/abs/2610.10126.

[19] Rasoul Akhavan Mahdavi, Thomas Humphries, and Florian Kerschbaum. Practical over-threshold multi-party private set intersection. Annual Computer Security Applications Conference (ACSAC), pages 772–784, 2020. URL https://doi.org/10.1145/3427228.3427260.

[20] Joel Miller, E. Glen Weyl, and Leon Erichsen. Beyond collusion resistance: Leveraging social information for plural funding and voting (COCM). SSRN Working Paper 4311507, 2022. URL https://papers.ssrn.com/sol3/papers.cfm?abstract_id=4311507.

[21] Luc Moreau and Paolo Missier. PROV-DM: The PROV data model. W3C Recommendation, 2013. URL https://www.w3.org/TR/prov-dm/.

[22] Qi Pang, Virginia Smith, and Wenting Zheng. Codetta: High-capacity, keyless, and undetectable multi-agent collusion. IACR ePrint 2026/2218 / arXiv:2609.28900, 2026. URL https://arxiv.org/abs/2609.28900.

[23] Ashwin Paranjape, Austin R. Benson, and Jure Leskovec. Motifs in temporal networks. ACM International Conference on Web Search and Data Mining (WSDM), pages 601–610, 2017. URL https://doi.org/10.1145/3018661.3018731.

[24] Eric A. Posner and E. Glen Weyl. *Radical Markets: Uprooting Capitalism and Democracy for a Just Society*. Princeton University Press, 2018.

[25] Christopher Small, Michael Bjorkegren, Timo Erkkilä, Lynette Shaw, and Colin Megill. Polis: Scaling deliberation by mapping high dimensional opinion spaces. *Recerca: Revista de Pensament i Anàlisi*, 26(2):1–26, 2021.

[26] Om Tailor. Audit the whisper: Detecting steganographic collusion in multi-agent LLMs. arXiv preprint arXiv:2510.04303, 2025. URL https://arxiv.org/abs/2510.04303.

[27] Michael Henry Tessler, Michiel A. Bakker, Daniel Jarrett, Hannah Sheahan, Martin J. Chadwick, Raphael Koster, Georgina Evans, Lucy Campbell-Gillingham, Tantum Collins, David C. Parkes, Matthew Botvinick, and Christopher Summerfield. AI can help humans find common ground in democratic deliberation. *Science*, 386(6719):eadq2852, 2024.

[28] Fabio Vitali and Valentina Pasqual. Provenance-enhanced statements in knowledge graphs. arXiv:2606.15246 [cs.AI], 2026. URL https://arxiv.org/abs/2606.15246.

[29] E. Glen Weyl, Puja Ohlhaver, and Vitalik Buterin. Decentralized society: Finding Web3's soul. SSRN Working Paper 4105763, 2022. URL https://papers.ssrn.com/sol3/papers.cfm?abstract_id=4105763.

[30] Stefan Wojcik, Sophie Hilgard, Nick Judd, Delia Mocanu, Stephen Ragain, Manu Hunziker, Keith Coleman, and Jay Baxter. Birdwatch: Crowd wisdom and bridging algorithms can inform understanding and reduce the spread of misinformation, 2022. URL https://arxiv.org/abs/2210.15723.

[31] Le Yang, Weijing You, Huiyang He, Kailiang Ji, and Jingqiang Lin. Practical traceable over-threshold multi-party private set intersection. Network and Distributed System Security Symposium (NDSS) / arXiv:2512.24652, 2025. URL https://arxiv.org/abs/2512.24652.

[32] Jay Yu, Austin Bennett, Billy Gao, and Rebecca Joseph. Evaluating voting design vulnerabilities for retroactive funding. arXiv preprint arXiv:2505.16068, 2025. URL https://arxiv.org/abs/2505.16068.

[33] Kaiyuan Zhang, Yuke Peng, Ke Jiang, and Yinqian Zhang. ActGov: Governing LLM agent actions via policy-constrained validation. arXiv preprint arXiv:2609.24446, 2026. URL https://arxiv.org/abs/2609.24446.